



EMERSON[™]
Motor Technologies

FIRE PUMP

For fire pump applications per NFPA^{®†} 20
where contaminants are minimal.

HP – 7.5 through 250 HP

Phase – Three Phase

RPM – 1800 and 3600

Voltage

- 575
- 208-230/460
- 200/400
- 230/460

Efficiency – Standard and Energy Efficient

Enclosure

- Open Dripproof (ODP)

Mounting

- Footed and Footless
- Vertical and Horizontal

Vertical Shaft Type – JP Close Coupled Pump Mounting



† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners

NFPA^{®†}: National Fire Protection Association

A worldwide leader in providing fire, electrical, and life safety to the public since 1896. The mission of the international nonprofit NFPA is to reduce the worldwide burden of fire and other hazards on the quality of life by providing and advocating scientifically-based consensus codes and standards, research, training and education. NFPA membership totals more than 75,000 individuals from around the world and more than 80 national trade and professional organizations.

For more information, go to www.nfpa.org.

Emerson fire pump products are fully compliant with federal motor efficiency requirements as described in the Energy Independence and Security Act of 2007 also known as EISA. All Emerson fire pump motors provide necessary identifying nameplate data.

EMERSON. CONSIDER IT SOLVED.[®]