


Split Phase Belted Fan & Blower

NEMA[®]† 48 Frame, Single & Two Speed




APPLICATIONS:

Designed to meet manufacturer's requirements for belted fans and blowers.

FEATURES:

- Resilient Base
- Class B Insulation Unless Otherwise Noted
- With Threaded Conduit Hole
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- Discount Symbol: DS-3HAC



Single Speed, Open Dripproof

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/3	1725	115/208-230	8438	\$301	Ball	48	6.8/3.1-3.4	2.0	.625	Auto	10.2	1.35	17	
1/4	1725	115	8000	\$127	Slv	48	5.3	1.5	.500	Auto	8.9	1.35	13	1, 3
	1725	115	840CV	\$128	Slv	48	4.8	1.6	.500	Auto	9.4	1.35	16	4, 6
	1725	115	2889	\$251	Ball	48	4.4	1.5	.500	Auto	9.9	1.35	21	7, 2
	1725	115/208-230	3617	\$151	Ball	48	5.2/2.5-2.6	1.5	.500	Auto	9.4	1.35	17	
1/3	1725	115	8100	\$132	Slv	48	6.7	1.5	.500	Auto	9.4	1.35	15	1, 3
	1725	115	841CV	\$133	Slv	48	5.6	1.6	.500	Auto	9.9	1.35	18	4, 6
	1725	115	2888	\$269	Ball	48	5.4	1.5	.500	Auto	9.9	1.35	18	7, 2
	1725	115/208-230	3623	\$178	Ball	48	6.6/3.1-3.3	1.9	.500	Auto	10.3	1.35	19	
1/2	1725	115	8200	\$158	Slv	48	8.7	1.5	.500	Auto	10.0	1.25	18	1, 3
	1725	115	1542C	\$168	Slv	48	7.8	1.6	.500	Auto	9.9	1.25	21	4
	1725	115	2887	\$305	Ball	48	7.8	1.5	.500	Auto	9.9	1.25	21	7, 2
	1725	115/208-230	3626	\$219	Ball	48	8.6/4.2-4.3	1.9	.500	Auto	10.3	1.25	20	
	1725	115/208-230	3627	\$219	Ball	48	8.6/4.2-4.3	1.9	.500	Auto	10.3	1.25	20	10
	1725	115/230	2695	\$323	Slv	48	7.8/3.9	1.5	.500	Auto	10.4	1.25	20	

Two Speed, Open Dripproof

HP	RPM	Volts	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wgt.	Notes
1/3	1725/1140	115	1786	\$389	Slv	48	5.8	1.5	.500	Auto	10.4	1.35	22	2
	1725/1140	230	1789	\$404	Slv	48	2.9	1.6	.500	Auto	10.4	1.35	22	2
1/4	1725	115	8505	\$192	Ball	48	5.0	1.5	.500	Auto	10.7	1.00	17	
	1725	115/208-230	3618	\$136	Ball	48Z	5.2/2.5-2.6	1.875	.500	Auto	9.3	1.35	14	

- Note 1 With Shaft Adapter For 5/8" Shaft.
 Note 2 Class A Insulation.
 Note 3 Combination Mounting Holes For NEMA[®] 48 & 56 Frame Dimensions
 Note 4 Canadian Standard — Connected CCWLE (Reversible)

- Note 6 Open, Ventilated
 Note 7 Enclosed Shell, Ventilation Through End Shields By Internal Fan.
 Note 10 Keyed Shaft

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners.