

# Permanent Split Capacitor Packaged Terminal A/C-Heat Pump 5.0" Diameter, Open, Air Over



## APPLICATIONS:

Designed to meet manufacturer's requirements for use in package terminal air conditioners or heat pump units.

## FEATURES:

- Sleeve Bearings Have All Angle Thrust System
- Designed for Use with 370V Capacitors
- Continuous Duty, Air Over
- Automatic Reset Thermal Overload Protector
- **Discount Symbol: DS-3HAC**

## Single Shaft, Direct Drive Blower

HP	RPM/Spds.	Volts	Catalog Number	List	Bearings	Cap MFD	Amps	Shaft N	Shaft XN	Shell XI	Total C	Mount	Ship Wgt.	Notes	OEM
1/30	1075/3	115	1374	\$250	Slv	5.0	.50	8.5	-	4.1	13.4	Resilient	10	1	TR
	1100/3	115	4125	\$200	Slv	4.0	.53	8.0	-	4.1	13.7	Resilient	6	1	IE
	1075/3	265	4126	\$162	Slv	3.0	.39	7.0	-	3.8	10.8	Flex	6		IE
1/20	1100/3	115	1676	\$281	Slv	5.0	.55	8.7	-	3.3	13.1	Resilient	9	1	TR
	1100/3	265	1965	\$172	Slv	4.0	.45	3.5	-	4.3	7.8	3 Lugs	10	3	AM
	1075/3	208-230	4136	\$212	Slv	5.0	.55	6.5	-	4.1	10.6	Flex	8		IE
	1075/3	265	1959	\$180	Slv	3.0	.40	6.5	-	4.1	10.6	Flex	8		IE
	1075/3	277	4137	\$186	Slv	4.0	.55	6.5	-	3.4	9.9	3 Lugs	8		IE
1/16	850/3	277	1678	\$190	Slv	4.0	.50	2.3	-	4.1	6.3	3 Lugs	12	1	TR
1/15	1075/3	265	1961	\$185	Slv	4.0	.60	7.0	-	3.8	10.8	Flex	12		IE
1/10	1050/3	277	1958	\$176	Slv	4.0	.65	4.0	-	4.1	8.1	Flex	12	1	
1/5	925/3	208-240	4129	\$176	Slv	6.0	1.9	7.0	-	4.6	11.6	Flex	12		IE
1/4	925/3	115	4130	\$191	Slv	12.5	6.0	7.0	-	4.8	11.8	Flex	13		IE
	1050/3	277	1962	\$201	Slv	7.5	1.6	7.0	-	5.1	12.6	Flex	13		IE
	1075/3	265	4131	\$199	Slv	10.0	1.6	5.25	-	4.8	10.1	Flex	13		IE

## Dual Shaft, Direct Drive Blower

HP	RPM/Spds.	Volts	Catalog Number	List	Bearings	Cap MFD	Amps	Shaft N	Shaft XN	Shell XI	Total C	Mount	Ship Wgt.	Notes	OEM
1/15	1100/3	115	1090	\$294	Slv	5.0	.8	9.7	10.8	3.8	25.4	Resilient	7		TR
1/12	1150/3	277	1960	\$189	Slv	5.0	.7	7.6	8.3	4.3	21.2	Hub Ring	9	1	IE
	1375/3	115-127	4127	\$206	Slv	6.0	1.35	8.0	8.25	3.8	21.2	Hub Ring	9	1	IE
1/10	1050/3	277	1957	\$192	Slv	4.0	.7	8.0	8.0	3.8	20.9	Hub Ring	9	1	
1/8	1500/3	277	1963	\$214	Slv	-	2.3	6.5	6.5	3.8	17.9	Resilient	10	2	
	1500/3	277	1964	\$218	Slv	4.0	.8	7.8	8.3	4.1	21.2	Resilient	10	1	
1/6	1050/3	115	1955	\$201	Slv	4.0	2.8	8.0	8.0	3.8	20.9	Hub Ring	11	1	
	1450/3	115-127	4128	\$221	Slv	5.0	2.55	8.0	8.3	4.1	21.4	Hub Ring	11	1	IE
	1625/4	115	8525	\$239	Slv	5.0	2.2	8.0	8.0	4.2	21.2	Resilient	12		

AM = Amana    IE = IEC    TR = Trane

Note 1    Capacitor Supplied  
Note 2    Shaded Pole

Note 3    Reversible

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners.