

# Vertical Holloshaft® High Thrust Motors – “P” Base, Single Phase Weather Protected Type I (WPI) Standard Efficient



AUR, AUC

## APPLICATIONS:

For use on Turbine, Mix Flow and Propeller Pumps.

## FEATURES:

- Equipped with Non-Reverse Ratchet
- 1.15 Service Factor, 40°C Ambient
- Class F Insulation
- Capacitor Start Design
- Corrosion Resistant Mill & Chemical Duty Paint
- Discount Symbol: DS-7VS

HP	RPM	Frame	Volts	Catalog Number	Type	List \$ w/NRR	List \$ w/SRC	Down Thrust (lbs.)	Base Dia. (in.)	Cplg Height (in.)	Cplg BX (in.)	Cplg Key Size	Ship Wt. (lbs.)	Notes
3	3600	213P	115/230	HS3C1PLE	AUR	\$1,884	\$1,780	2200	10	17-9/16	1	1/4	210	
	1800	215P	115/230	HS3C2PLE	AUR	\$1,946	\$1,828	2500	10	17-9/16	1	1/4	220	
5	3600	215P	230	HS5C1KLE	AUR	\$2,036	\$1,918	2200	10	17-9/16	1	1/4	220	
	1800	254UP	230	HS5C2KLE	AUC	\$2,466	\$2,326	2500	10	23-3/8	1	1/4	265	
7-1/2	3600	254UP	230	HS7C1KLE	AUC	\$2,904	\$2,764	2600	10	23-3/8	1	1/4	265	
	1800	256UP	230	HS7C2KLE	AUC	\$3,336	\$3,176	3300	10	23-3/8	1	1/4	300	

NOTE: Alternative Coupling Sizes per Frame Size are listed beginning on Page 300.

Most stock VHS Motors include a Non-Reverse Ratchet (NRR), as indicated by their Catalog Number. To order a Motor with a Self-Release Coupling (SRC), add an "N" as the last character in the Catalog Number. Example: HO50S2BLG includes NRR, HO50S2BLGN is SRC.