

GENERAL PURPOSE UNIMOUNT  
 GENERAL PURPOSE HOSTILE DUTY  
 GENERAL PURPOSE CORRO-DUTY  
 GENERAL PURPOSE 841 PLUS  
 GENERAL PURPOSE e-LINE  
 GENERAL PURPOSE OPEN DRIPPROOF  
 GENERAL PURPOSE HAZARDOUS LOCATION  
 GENERAL PURPOSE AUTOMOTIVE DUTY  
 COOLING TOWER DUTY  
 HAZARDOUS LOCATION  
 C-FACE MOTORS  
 VARIABLE FREQUENCY

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Corro-Duty® NEMA Premium† Efficient – IE3



TCE

## APPLICATIONS:

For pulp & paper, mill & chemical and any other severe duty environments found in the process industries.

## FEATURES:

- Class F Insulation, Class B Rise At Full Load On 60 Hertz Sine Wave Power
- All Cast Iron Construction (Steel Frame & Fan Cover On 140 Frame)
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate (with CE Mark) & Zinc Plated Hardware
- Shaft Slinger On Pulley End For IP54 Protection
- Precision Balance (< 0.08 In/Sec Vibration)
- 40°C Ambient, NEMA® Design B Performance On 60 Hertz Sine Wave Power
- Regreaseable Bearings 180 Frame & Up, Lifting Provisions 180 Frame & Up
- Double Shielded Bearings 140-360, Open On 400-440
- Oversized Conduit Box - 1 Size Larger Than NEMA Standard
- Cast Iron Inner Bearing Caps (180 Frame & Larger)
- Field Convertible To F2 Mounting 180 Frame & Larger
- Condensation Drains With Plastic Plugs
- Conversion Kits: C&D Flanges, Drip Cover Kits (except 320-360), See Pages 260-266

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	1800	230/460	143T	C1P2B	\$1,144	DS-3CE	1.15	12.6	55	85.5	3/1.5	
	1800	575	143T	C1P2G	\$1,144	DS-3CE	1.15	12.6	55	85.5	1.1	
	1200	230/460	145T	C1P3B	\$1,265	DS-3CE	1.15	13.9	75	82.5	3.5/1.8	
	1200	575	145T	C1P3G	\$1,265	DS-3CE	1.15	13.9	75	82.5	1.4	
	900	230/460	182T	C1P4B	\$1,678	DS-3CE	1.15	16.4	75	74.0	4.5/2.2	
1-1/2	3600	230/460	143T	C32P1B	\$1,041	DS-3CE	1.15	12.6	55	84.0	3.9/1.9	
	1800	230/460	145T	C32P2B	\$1,165	DS-3CE	1.15	13.9	70	86.5	4.3/2.1	
	1800	575	145T	C32P2G	\$1,165	DS-3CE	1.15	13.9	70	86.5	1.7	
	1200	230/460	182T	C32P3B	\$1,480	DS-3CE	1.15	16.2	100	87.5	4.7/2.3	
	1200	575	182T	C32P3G	\$1,480	DS-3CE	1.15	16.2	100	87.5	1.8	
2	900	230/460	184T	C32P4B	\$1,844	DS-3CE	1.15	16.2	100	80.0	6.2/3.1	
	3600	230/460	145T	C2P1B	\$1,172	DS-3CE	1.15	12.6	70	86.5	4.9/2.4	
	1800	230/460	145T	C2P2B	\$1,218	DS-3CE	1.15	13.9	80	86.5	5.7/2.8	
	1800	575	145T	C2P2G	\$1,218	DS-3CE	1.15	13.9	125	86.5	2.2	
	1200	230/460	184T	C2P3B	\$1,500	DS-3CE	1.15	16.2	125	88.5	6.2/3.1	
3	1200	575	184T	C2P3G	\$1,500	DS-3CE	1.15	16.2	110	88.5	2.5	
	900	230/460	213T	C2P4B	\$2,017	DS-3CE	1.15	20.8	110	82.5	7.4/3.7	
	3600	230/460	182T	C3P1B	\$1,467	DS-3CE	1.15	16.2	100	87.5	7.8/3.9	
	1800	230/460	182T	C3P2B	\$1,542	DS-3CE	1.15	16.2	100	89.5	7.8/3.9	
	1800	575	182T	C3P2G	\$1,542	DS-3CE	1.15	16.2	100	89.5	3.1	
5	1200	230/460	213T	C3P3B	\$2,167	DS-3CE	1.15	19.6	160	89.5	8.8/4.4	
	1200	575	213T	C3P3G	\$2,167	DS-3CE	1.15	19.6	160	89.5	3.5	
	900	230/460	215T	C3P4B	\$2,771	DS-3CE	1.15	19.6	160	84.0	11.3/5.6	
	3600	230/460	184T	C5P1B	\$1,806	DS-3CE	1.15	16.2	110	89.5	12.6/6.3	
	1800	230/460	184T	C5P2B	\$1,568	DS-3CE	1.15	16.2	120	90.2	12.5/6.3	
7-1/2	1800	575	184T	C5P2G	\$1,568	DS-3CE	1.15	16.2	120	89.5	5	
	1200	230/460	215T	C5P3B	\$2,196	DS-3CE	1.15	19.6	190	90.2	14/7	
	1200	575	215T	C5P3G	\$2,196	DS-3CE	1.15	19.6	190	89.5	5.6	
	900	230/460	254T	C5P4B	\$3,827	DS-3CE	1.15	25.0	190	89.5	15.2/7.6	
	3600	230/460	213T	C7P1B	\$2,358	DS-3CE	1.15	19.6	160	91.7	17.9/8.9	14
10	1800	230/460	213T	C7P2B	\$1,978	DS-3CE	1.15	19.6	160	91.7	18.6/9.3	
	1800	575	213T	C7P2G	\$1,978	DS-3CE	1.15	19.6	160	91.7	7.5	
	1200	230/460	254T	C7P3B	\$3,145	DS-3CE	1.15	25.0	300	91.7	20.2/10.1	14
	1200	575	254T	C7P3G	\$3,145	DS-3CE	1.15	25.0	300	91.7	7.9	14
	3600	230/460	215T	C10P1B	\$2,509	DS-3CE	1.15	19.6	185	91.7	23.5/11.8	
1800	230/460	215T	C10P2B	\$2,368	DS-3CE	1.15	19.6	200	91.7	23.9/12		

Note 14 NEMA® Design A

† All marks shown within this document are properties of their respective owners.



# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Corro-Duty® NEMA Premium<sup>†</sup> Efficient – IE3



GENERAL PURPOSE UNIMOUNT  
GENERAL PURPOSE HOSTILE DUTY  
GENERAL PURPOSE CORRO-DUTY  
GENERAL PURPOSE 841 PLUS  
GENERAL PURPOSE e-LINE  
GENERAL PURPOSE OPEN DRIPPROOF  
GENERAL PURPOSE HAZARDOUS LOCATION  
GENERAL PURPOSE AUTOMOTIVE DUTY  
COOLING TOWER DUTY  
HAZARDOUS LOCATION  
C-FACE MOTORS  
VARIABLE FREQUENCY

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
10	1800	575	215T	C10P2G	\$2,368	DS-3CE	1.15	19.6	200	91.7	9.6	
	1200	230/460	256T	C10P3B	\$4,086	DS-3CE	1.15	25.0	340	91.7	25/12.5	14
	1200	575	256T	C10P3G	\$4,086	DS-3CE	1.15	25.0	340	91.7	10	14
15	3600	230/460	254T	C15P1B	\$3,212	DS-3CE	1.15	25.0	320	91.7	35/17.7	14
	1800	230/460	254T	C15P2B	\$3,017	DS-3CE	1.15	25.0	320	92.4	37/18.4	
	1800	575	254T	C15P2G	\$3,017	DS-3CE	1.15	25.0	320	92.4	14.6	
	1200	230/460	284T	C15P3B	\$4,684	DS-3CE	1.15	27.0	400	91.7	38/19	14
	1200	575	284T	C15P3G	\$4,684	DS-3CE	1.15	27.0	400	92.4	15.2	14
20	3600	230/460	256T	C20P1B	\$3,748	DS-3CE	1.15	25.0	420	92.4	46/23	14
	1800	230/460	256T	C20P2B	\$3,238	DS-3CE	1.15	25.0	360	93.0	48/24	
	1800	575	256T	C20P2G	\$3,238	DS-3CE	1.15	25.0	360	93.0	19	
	1200	230/460	286T	C20P3B	\$6,365	DS-3CE	1.15	27.0	420	92.4	50/25.1	14
	1200	575	286T	C20P3G	\$6,365	DS-3CE	1.15	27.0	420	92.4	20	14
25	3600	460	284TS	C25P1CS	\$4,505	DS-3CE	1.15	26.3	320	92.4	29.8	14
	1800	460	284T	C25P2C	\$4,238	DS-3CE	1.15	27.0	400	93.0	29.6	
	1800	575	284T	C25P2G	\$4,238	DS-3CE	1.15	27.0	400	93.6	23.5	
	1200	460	324T	C25P3C	\$6,651	DS-3CE	1.15	30.8	515	93.0	29.4	
	1200	575	324T	C25P3G	\$6,651	DS-3CE	1.15	30.8	515	93.0	23.5	
30	3600	460	286TS	C30P1CS	\$5,494	DS-3CE	1.15	26.3	425	92.4	34	
	1800	460	286T	C30P2C	\$5,033	DS-3CE	1.15	27.0	455	93.6	35	
	1800	575	286T	C30P2G	\$5,033	DS-3CE	1.15	27.0	455	93.6	27.6	
	1200	460	326T	C30P3C	\$8,576	DS-3CE	1.15	30.8	595	93.6	35	
	1200	575	326T	C30P3G	\$8,576	DS-3CE	1.15	30.8	595	93.0	28.1	
40	3600	460	324TS	C40P1CS	\$7,550	DS-3CE	1.15	29.3	465	93.6	46	14
	3600	575	324TS	C40P1GS	\$7,550	DS-3CE	1.15	29.3	465	93.0	38	
	1800	460	324T	C40P2C	\$6,585	DS-3CE	1.15	30.8	515	94.1	46	
	1800	575	324T	C40P2G	\$6,585	DS-3CE	1.15	30.8	515	94.1	37	
	1200	460	364T	C40P3C	\$10,692	DS-3CE	1.15	33.0	860	94.1	46	
50	1200	575	364T	C40P3G	\$10,692	DS-3CE	1.15	33.0	860	94.1	37	
	3600	460	326TS	C50P1CS	\$7,913	DS-3CE	1.15	29.3	555	93.0	56	
	1800	460	326T	C50P2C	\$7,731	DS-3CE	1.15	30.8	595	94.5	56	
	1800	575	326T	C50P2G	\$7,731	DS-3CE	1.15	30.8	595	94.5	45	
	1200	460	365T	C50P3C	\$11,387	DS-3CE	1.15	33.0	875	94.1	58	
60	1200	575	365T	C50P3G	\$11,387	DS-3CE	1.15	33.0	875	94.1	46	
	3600	460	364TS	C60P1CS	\$11,484	DS-3CE	1.15	30.9	855	93.0	68	14
	1800	460	364T	C60P2C	\$10,363	DS-3CE	1.15	33.0	855	95.0	69	14
	1800	460	364TS	C60P2CS	\$10,363	DS-3CE	1.15	30.9	855	95.0	69	14
	1800	575	364T	C60P2G	\$10,363	DS-3CE	1.15	33.0	855	95.0	55	14
75	1200	460	404T	C60P3C	\$15,245	DS-3CE	1.15	36.5	1245	94.5	70	
	3600	460	365TS	C75P1CS	\$12,837	DS-3CE	1.15	30.9	915	93.6	84	14
	3600	575	365TS	C75P1GS	\$12,837	DS-3CE	1.15	30.9	915	93.6	67	
	1800	460	365T	C75P2C	\$12,110	DS-3CE	1.15	33.0	925	95.4	84	
	1800	460	365TS	C75P2CS	\$12,110	DS-3CE	1.15	30.9	925	95.4	84	
	1800	575	365T	C75P2G	\$12,110	DS-3CE	1.15	33.0	925	95.4	68	
1200	460	405T	C75P3C	\$18,554	DS-3CE	1.15	38.0	1250	94.5	87		

Note 14 NEMA<sup>®</sup> Design A

† All marks shown within this document are properties of their respective owners.



GENERAL PURPOSE UNIMOUNT  
 GENERAL PURPOSE HOSTILE DUTY  
 GENERAL PURPOSE CORRO-DUTY  
 GENERAL PURPOSE 841 PLUS  
 GENERAL PURPOSE e-LINE  
 GENERAL PURPOSE OPEN DRI/PROOF  
 GENERAL PURPOSE HAZARDOUS LOCATION  
 GENERAL PURPOSE AUTOMOTIVE DUTY  
 COOLING TOWER DUTY  
 HAZARDOUS LOCATION  
 C-FACE MOTORS  
 VARIABLE FREQUENCY

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Corro-Duty® NEMA Premium<sup>†</sup> Efficient – IE3



TCE

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
100	3600	460	405TS	C100P1CS	\$16,289	DS-3CE	1.15	35.0	1250	94.5	109	
	1800	460	405T	C100P2C	\$15,166	DS-3CE	1.15	38.0	1250	95.4	113	
	1200	460	444T	C100P3C	\$21,019	DS-3CE	1.15	45.9	1660	95.4	124	
	1200	460	444T	C100P3CB	\$21,019	DS-3CE	1.15	45.9	1660	95.4	124	09
	1200	575	444T	C100P3G	\$21,019	DS-3CE	1.15	45.9	1660	95.4	99	
125	3600	460	444TS	C125P1CS	\$19,142	DS-3CE	1.15	42.1	1625	95.0	145	12
	1800	460	444T	C125P2C	\$17,928	DS-3CE	1.15	45.9	1900	95.4	147	
	1800	460	444T	C125P2CB	\$17,928	DS-3CE	1.15	45.9	1690	95.4	144	09
	1800	460	444TS	C125P2CS	\$17,928	DS-3CE	1.15	42.1	1690	95.4	147	
	1200	460	445T	C125P3C	\$23,748	DS-3CE	1.15	45.9	1600	95.8	155	
	1200	460	445T	C125P3CB	\$23,748	DS-3CE	1.15	45.9	1750	95.4	155	09
	1200	575	445T	C125P3G	\$23,748	DS-3CE	1.15	45.9	1750	95.8	124	
150	3600	460	445TS	C150P1CS	\$22,440	DS-3CE	1.15	42.1	1775	95.0	176	12
	1800	460	445T	C150P2C	\$21,004	DS-3CE	1.15	45.9	1800	95.8	172	
	1800	460	445T	C150P2CB	\$21,004	DS-3CE	1.15	45.9	1800	95.8	172	09
	1800	460	445TS	C150P2CS	\$21,004	DS-3CE	1.15	42.1	1800	95.8	172	
	1800	575	445T	C150P2G	\$21,004	DS-3CE	1.15	45.9	1800	95.8	137	
	1200	460	447T	C150P3C	\$26,775	DS-3CE	1.15	49.4	2100	96.2	181	
	1200	460	447T	C150P3CB	\$26,775	DS-3CE	1.15	49.4	2100	96.2	176	09
	1200	575	447T	C150P3G	\$26,775	DS-3CE	1.15	49.4	2100	96.2	145	
	200	3600	460	447TS	C200P1CS	\$26,575	DS-3CE	1.15	45.6	2185	95.4	220
200	1800	460	447T	C200P2C	\$25,268	DS-3CE	1.15	45.6	2200	96.2	224	
	1800	460	447T	C200P2CB	\$25,268	DS-3CE	1.15	45.6	2200	96.2	224	
	1800	460	447TS	C200P2CS	\$25,268	DS-3CE	1.15	45.6	2200	96.2	224	
	1800	575	447T	C200P2G	\$25,268	DS-3CE	1.15	49.4	2200	96.2	180	
	1200	460	449T	C200P3C	\$29,851	DS-6S	1.15	55.1	2400	95.8	224	
	250	3600	460	449TS	C250P1CS	\$35,294	DS-6S	1.15	51.4	2700	95.8	267
250	1800	460	449T	C250P2C	\$31,395	DS-6S	1.15	55.1	2700	96.2	273	
	1200	460	449T	C250P3C	\$32,202	DS-6S	1.15	55.1	2800	95.8	280	
	300	3600	460	449TS	C300P1CS	\$37,984	DS-6S	1.15	51.4	2750	95.8	322
300	1800	460	449T	C300P2C	\$32,003	DS-6S	1.15	55.1	2850	96.2	326	
	1200	460	449T	C300P3C	\$37,808	DS-6S	1.15	55.1	2800	95.8	334	
	350	3600	460	449TS	C350P1CS	\$43,240	DS-6S	1.15	51.4	2800	95.8	374
350	1800	460	449T	C350P2C	\$35,130	DS-6S	1.15	55.1	2950	96.2	381	
	400	3600	460	449TS	C400P1CS	\$48,946	DS-6S	1.15	51.4	2900	95.8	426
400	1800	460	449T	C400P2C	\$37,451	DS-6S	1.15	55.1	3025	96.2	434	

Note 09 Roller Bearing  
 Note 12 Unidirectional Fan - CCW direction facing opposite drive end (FODE)

† All marks shown within this document are properties of their respective owners.

