


GENERAL PURPOSE UNIMOUNT
GENERAL PURPOSE HOSTILE DUTY
GENERAL PURPOSE CORRO-DUTY
GENERAL PURPOSE 841 PLUS
GENERAL PURPOSE e-LINE
GENERAL PURPOSE OPEN DRIIPROOF
GENERAL PURPOSE HAZARDOUS LOCATION
GENERAL PURPOSE AUTOMOTIVE DUTY
COOLING TOWER DUTY
HAZARDOUS LOCATION
C-FACE MOTORS
VARIABLE FREQUENCY

General Purpose Three Phase Totally Enclosed Fan Cooled (TEFC) Severe Duty NEMA Premium^{®†} Efficient – IE3, All Cast Iron e|LINE™



APPLICATIONS:

For severe duty environments found in the pulp & paper, lumber, aggregates, mining, chemical and other industries.

FEATURES:

- Fully Compliant with EISA Standards
- INVERTER GRADE[®] Insulation System to Meet NEMA^{®†} MG-1 Part 31 Specification on 140 to 280 Frames, NEMA^{®†} MG-1 Part 30 Specification on 320 to 440 Frames
- 10:1 Variable Torque; 5:1 Constant Torque on Inverter Power
- 40°C Ambient, Continuous Duty
- Double Shielded Bearings through 280 Frame, Open Bearings 320 to 440 Frame
- Double Drilled Feet to Accommodate Mounting Flexibility
- Vacuum Pressure Impregnation (VPI) Insulation
- NEMA^{®†} Design B Performance
- Shaft Seal V-Ring
- Lifting Provisions
- Field Convertible to F2 Mounting
- Corrosion Resistant Mill & Chemical Duty Paint
- Division 2 Nameplated
- Stainless Steel Nameplate & Zinc Plated Hardware
- Dual Voltage Nameplated @ 60 & 50 Hz
- Full 50 Hz Power at Rated HP
- DOE Compliance Certification - CC030A
- CE Mark on Nameplate
- CSA^{®†} 390 Certified
- Field Convertible C-Face Kits Available
- UL^{®†} Component Recognized

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps
1	1800	208-230/460	143T	ELT1P2D	\$415	DS-3ELP	1.15	13.6	57	86.5	3.3-3.0/1.5
	1200	208-230/460	145T	ELT1P3D	\$564	DS-3ELP	1.15	13.6	62	82.5	3.5-3.2/1.6
1-1/2	3600	208-230/460	143T	ELT32P1D	\$478	DS-3ELP	1.15	13.6	57	84	4.4-4.0/2.0
	1800	208-230/460	145T	ELT32P2D	\$460	DS-3ELP	1.15	13.6	62	86.5	5.1-4.6/2.3
	1200	208-230/460	182T	ELT32P3D	\$626	DS-3ELP	1.15	16	126	87.5	5.2-4.7/2.3
2	3600	208-230/460	145T	ELT2P1D	\$568	DS-3ELP	1.15	14	62	85.5	5.7-5.2/2.6
	1800	208-230/460	145T	ELT2P2D	\$504	DS-3ELP	1.15	14	64	86.5	6.7-6.0/3.0
	1200	208-230/460	184T	ELT2P3D	\$697	DS-3ELP	1.15	16	13	88.5	6.8-6.2/3.1
3	3600	208-230/460	182T	ELT3P1D	\$639	DS-3ELP	1.15	16	112	86.5	8.4-7.6/3.8
	1800	208-230/460	182T	ELT3P2D	\$565	DS-3ELP	1.15	16	123	89.5	9.3-8.4/4.2
	1200	208-230/460	213T	ELT3P3D	\$863	DS-3ELP	1.15	20	190	89.5	9.7-8.8/4.4
5	3600	208-230/460	184T	ELT5P1D	\$802	DS-3ELP	1.15	16	123	88.5	13.5-12.2/6.1
	1800	208-230/460	184T	ELT5P2D	\$657	DS-3ELP	1.15	16	130	89.5	14.9-13.5/6.7
	1200	208-230/460	215T	ELT5P3D	\$1,236	DS-3ELP	1.15	20	201	89.5	16.4-14.8/7.4
7-1/2	3600	208-230/460	213T	ELT7P1D	\$993	DS-3ELP	1.15	20	183	89.5	20.1-18.1/9.1
	1800	208-230/460	213T	ELT7P2D	\$898	DS-3ELP	1.15	20	207	91.7	21.3-19.2/9.6
	1200	208-230/460	254T	ELT7P3D	\$1,649	DS-3ELP	1.15	25.4	306	91	23.2-21.0/10.5
10	3600	208-230/460	215T	ELT10P1D	\$1,164	DS-3ELP	1.15	20	196	90.2	26.5-24.0/12.0
	1800	208-230/460	215T	ELT10P2D	\$1,085	DS-3ELP	1.15	20	216	91.7	28.4-25.7/12.8
	1200	208-230/460	256T	ELT10P3D	\$1,992	DS-3ELP	1.15	25.4	351	91	30.9-28.0/14.0
15	3600	208-230/460	254T	ELT15P1D	\$1,599	DS-3ELP	1.15	25.4	328	91	39.9-36.1/18.0
	1800	208-230/460	254T	ELT15P2D	\$1,438	DS-3ELP	1.15	25.4	373	92.4	40.2-36.4/18.2
	1200	208-230/460	284T	ELT15P3D	\$2,665	DS-3ELP	1.15	28.8	423	91.7	43.7-39.5/19.7
20	3600	208-230/460	256T	ELT20P1D	\$1,980	DS-3ELP	1.15	25.4	373	91	52.0-47.0/23.5
	1800	208-230/460	256T	ELT20P2D	\$1,773	DS-3ELP	1.15	25.4	417	93	53.3-48.2/24.1
	1200	208-230/460	286T	ELT20P3D	\$3,228	DS-3ELP	1.15	28.8	445	91.7	58.2-52.6/26.3
25	3600	208-230/460	284TS	ELT25P1DS	\$2,429	DS-3ELP	1.15	27.6	432	91.7	64.5-58.3/29.2
	1800	208-230/460	284T	ELT25P2D	\$2,127	DS-3ELP	1.15	28.8	461	93.6	66.2-59.9/29.9
	1200	208-230/460	324T	ELT25P3D	\$3,841	DS-3ELP	1.15	30.3	613	93	72.7-65.7/32.9

† All marks shown within this document are properties of their respective owners.



General Purpose Three Phase Totally Enclosed Fan Cooled (TEFC) Severe Duty NEMA Premium^{®†} Efficient – IE3, All Cast Iron e|LINE™



**NEMA
Premium**

GENERAL PURPOSE
UNIMOUNT™
GENERAL PURPOSE
HOSTILE DUTY
GENERAL PURPOSE
CORRO-DUTY™
GENERAL PURPOSE
S&I PLUS™
GENERAL PURPOSE
e|LINE™
GENERAL PURPOSE
OPEN DRIPPROOF
GENERAL PURPOSE
HAZARDOUS LOCATION
GENERAL PURPOSE
AUTOMOTIVE DUTY
COOLING TOWER
DUTY
HAZARDOUS
LOCATION
C-FACE
MOTORS
VARIABLE
FREQUENCY

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps
30	3600	208-230/460	286TS	ELT30P1DS	\$2,848	DS-3ELP	1.15	27.6	456	91.7	76.5-69.2/34.6
	1800	208-230/460	286T	ELT30P2D	\$2,481	DS-3ELP	1.15	28.8	478	93.6	79.4-71.8/35.9
	1200	208-230/460	326T	ELT30P3D	\$4,532	DS-3ELP	1.15	31.9	659	93	86.1-77.9/38.9
40	3600	208-230/460	324TS	ELT40P1DS	\$3,680	DS-3ELP	1.15	30.3	628	92.4	100.1-90.6/45.3
	1800	208-230/460	324T	ELT40P2D	\$3,239	DS-3ELP	1.15	31.9	672	94.1	102.9-93.1/46.5
	1200	208-230/460	364T	ELT40P3D	\$6,104	DS-3ELP	1.15	34.3	807	94.1	107.9-97.6/48.8
50	3600	208-230/460	326TS	ELT50P1DS	\$4,735	DS-3ELP	1.15	30.3	686	93	127.2-115.0/57.5
	1800	208-230/460	326T	ELT50P2D	\$3,977	DS-3ELP	1.15	31.9	697	94.5	126.6-114.5/57.2
	1200	208-230/460	365T	ELT50P3D	\$7,032	DS-3ELP	1.15	34.3	836	94.1	134.9-122.0/61.0
60	3600	208-230/460	364TS	ELT60P1DS	\$6,321	DS-3ELP	1.15	32.1	811	93.6	153.4-138.7/69.4
	1800	208-230/460	364T	ELT60P2D	\$5,782	DS-3ELP	1.15	34.3	831	95	154.7-139.9/69.9
	1200	208-230/460	404T	ELT60P3D	\$8,285	DS-3ELP	1.15	39	1067	94.5	153.7-139.0/69.5
75	3600	208-230/460	365TS	ELT75P1DS	\$7,942	DS-3ELP	1.15	32.1	858	93.6	191.7-173.4/86.7
	1800	208-230/460	365T	ELT75P2D	\$7,354	DS-3ELP	1.15	34.3	880	95.4	192.6-174.1/87.1
	1200	208-230/460	405T	ELT75P3D	\$9,768	DS-3ELP	1.15	39	1173	94.5	204.0-184.5/92.2
100	3600	208-230/460	405TS	ELT100P1DS	\$10,637	DS-3ELP	1.15	36	1162	94.1	257.3-232.6/116.3
	1800	208-230/460	405T	ELT100P2D	\$9,063	DS-3ELP	1.15	39	1265	95.4	256.7-232.2/116.1
	1200	208-230/460	444T	ELT100P3D	\$13,374	DS-3ELP	1.15	46.1	1841	95	267.2-241.7/120.8
125	3600	208-230/460	444TS	ELT125P1DS	\$14,096	DS-3ELP	1.15	42.3	1750	95	318.5-288.1/144.0
	1800	208-230/460	444T	ELT125P2D	\$12,014	DS-3ELP	1.15	46.1	1731	95.4	317.2-286.8/143.4
	1200	208-230/460	445T	ELT125P3D	\$16,292	DS-3ELP	1.15	46.1	1956	95	330.0-298.5/149.2
150	3600	460	445TS	ELT150P1FS	\$17,074	DS-3ELP	1.15	42.3	1803	95	172.8
	1800	460	445T	ELT150P2F	\$14,036	DS-3ELP	1.15	46.1	1850	95.8	171.4
	1200	460	447T	ELT150P3F	\$18,418	DS-3ELP	1.15	54.6	2324	95.8	179.7
200	3600	460	447TS	ELT200P1FS	\$21,622	DS-3ELP	1.15	50.8	2242	95.4	224.3
	1800	460	447T	ELT200P2F	\$17,137	DS-3ELP	1.15	54.6	2361	96.2	230.2
250	3600	460	449TS	ELT250P1FS	\$32,625	DS-3ELP	1.15	50.8	2498	95.8	279.2
	1800	460	449T	ELT250P2F	\$25,225	DS-3ELP	1.15	54.6	2520	96.2	274.9

† All marks shown within this document are properties of their respective owners.

*Based on Test Data at Time of Publication

