

Permanent Split Capacitor & Shaded Pole Flex Mount Direct Drive Fan & Blower 5.0" & 5.6" Diameter, Open, Air Over




APPLICATIONS:

Designed to meet manufacturer's requirements for use on direct drive fan & blowers with flexible ear mounts.

FEATURES:

- Class B Insulation Unless Noted
- 5.0" Diameter Motors CWLE Rotation
- 5.6" Diameter Motors Reversible Rotation
- Sleeve Bearings, All Angle Thrust System
- Continuous Duty, Air Over
- 24" Leads
- Automatic Reset Thermal Overload Protector
- PSC Motors Designed For 370V Capacitors
- **Discount Symbol: DS-3HAC**



Shaded Pole 5.0" Diameter

HP	RPM/ Spd.	Volts	Catalog Number	List	Cap MFD	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes	OEM
1/5	1050/1	115	2867	\$145	N/A	6.5	3.8	4.6	8.3	10	H22	MI

Permanent Split Capacitor 5.6" Diameter

HP	RPM/ Spd.	Volts	Catalog Number	List	Cap MFD	Amps	Shaft N	Shell XI	Total C	Ship Wgt.	Notes	OEM
1/4	1075/3	115	3783	\$205	5.0	3.8	5.0	4.3	9.3	11		
	1075/3	208-230	3784	\$218	5.0	1.7	5.0	4.3	9.3	10		
1/3	825/3	230	8052	\$191	15.0	1.9	2.5	4.8	7.3	14		LE
	1000/4	115	9377	\$222	5.0	6.0	5.3	4.6	9.8	13		
	1075/3	115	3785	\$214	7.5	5.0	5.0	4.6	9.6	13		
	1075/3	208-230	3786	\$231	5.0	2.4	5.0	4.3	9.3	12		
1/2	1075/3	115	3787	\$245	10.0	7.5	5.0	5.6	10.7	18		
	1075/3	208-230	3788	\$259	7.5	3.3	5.0	5.3	10.3	17		

LE = Lennox MI = Miller

Note H22 Flex Mount is Removable

† All marks shown within this document are properties of their respective owners