


Special Application Close Coupled Pump Three Phase Div. 1 Hazardous Duty, Dual Label



L4

APPLICATIONS:

For the specific requirements of centrifugal pumps located in hazardous locations as defined by Class and Group.

FEATURES:

- UL[®] Listed & CSA[®] Certified
- Cast Iron Frame, End Brackets & Conduit Box
- Stainless Steel Nameplate & Zinc Plated Hardware
- Cast Iron Inner Bearing Caps
- 40°C Ambient, NEMA[®] Design B Performance On 60 Hertz Sine Wave Power
- Class I Group D, Class II Group F&G, T3B
- Regreasable Bearings and Lifting Provisions
- Double Shielded Bearings
- 1.0 Service Factor At 60 Hertz
- Class F Insulation, Listed For Ambients -25°C To +40°C
- "JM" Shaft For Mechanical Seal

Energy Efficient

HP	RPM	Voltage	Frame	Catalog Number	Class I Group	Class II Group	Temp Code	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
3	3600	230/460	182JM	XJ3E1BM	D	F G	T3B	\$1,080	DS-3PT	17.5	104	80.0	7.8/3.9	
	1800	230/460	182JM	XJ3E2BM	D	F G	T3B	\$1,113	DS-3PT	17.5	80	80.0	8.2/4.1	
5	3600	230/460	184JM	XJ5E1BM	D	F G	T3B	\$1,410	DS-3PT	18.5	102	82.5	12.2/6.1	
	1800	230/460	184JM	XJ5E2BM	D	F G	T3B	\$1,306	DS-3PT	18.5	150	85.5	12.8/6.4	

† All non-Emerson Electric Co. marks shown within this document are properties of their respective owners

