

Special Application Commercial Pump Three Phase Open Dripproof (ODP) C-Face



APPLICATIONS:

For use on chiller, condensate, and other HVAC duty pumps, booster and irrigation pumps, dishwasher and part washer pumps, watering and de-watering pumps, and other commercial duty pumping applications.

FEATURES:

- "CE" Mark on nameplate (140 Frame and Larger)
- Double Sealed Ball Bearings on All 56-Frame Commercial Duty Pump Motors; Double Shielded Ball Bearings on All Others
- Continuous Duty
- 60 Hertz & 60/50 Hertz
- 50/60 Hz Motors have 1.0 S.F. on 50 Hz
- 40°C Ambient
- Suitable for Wye-Delta start 250-Frame and larger
- NEMA[®] "C" Flange Mounting
- Shaft Threads for 56J Mount: 7/16-20 UNC-2A
- Premium 303 S.S. on 56J; Mount & Carbon Steel on All Others

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	Base (Feet)	SF	"C" Dim (in.)	Ship Wt.	Dripcover Kit	Max. Amps	Notes
3/4	3600	208-230/460	56C	EE508	\$444	DS-3F	No	1.50	11.3	25	DC48	3.8-3.6/1.8	03
	3600	208-230/460	56J	EE446	\$449	DS-3F	No	1.50	11.8	25	DC48	3.8-3.6/1.8	03
	3600	208-230/460	56J	EE446B	\$454	DS-3F	Rigid	1.50	11.6	25	DC56	3.7-3.6/1.8	03
	1800	208-230/460	56C	D34S2ACR	\$366	DS-3F	No	1.25	11.4	22	DC56	2.8-2.7/1.4	FL
	1200	208-230/460	56C	D34S3DCR	\$704	DS-3F	No	1.15	12.0	30	DC56	3.4-3.5/1.7	26, FL
1	3600	208-230/460	56C	EE511	\$464	DS-3F	No	1.40	11.6	26	DC48	4.6-4.6/2.3	03
	3600	208-230/460	56C	EE511B	\$469	DS-3F	Rigid	1.40	11.1	26	DC56	4.4-4.2/2.1	03
	3600	208-230/460	56J	EE506	\$469	DS-3F	No	1.40	12.1	26	DC48	4.6-4.6/2.3	03
	3600	208-230/460	56J	EE506B	\$474	DS-3F	Rigid	1.40	11.6	26	DC56	4.4-4.2/2.1	03
	1800	208-230/460	56HC	D1S2AHC	\$353	DS-3F	Rigid	1.25	12.0	28	DC56	3.2-3.0/1.5	FL
1-1/2	3600	208-230/460	56C	EE609	\$537	DS-3F	No	1.30	11.4	27	DC56	6.0-5.8/2.9	03
	3600	208-230/460	56C	D32S1AHC	\$541	DS-3F	Rigid	1.15	11.9	27	DC56	4.7-4.4/2.2	26, FL
	3600	208-230/460	56J	EE607	\$541	DS-3F	No	1.30	11.9	27	DC56	6.0-5.8/2.9	03
	3600	208-230/460	56J	EE607B	\$546	DS-3F	Rigid	1.30	11.9	27	DC56	6.0-5.8/2.9	03
	1800	208-230/460	56C	D32S2ACR	\$482	DS-3F	No	1.25	12.4	32	DC56	4.9-5.0/2.5	03, FL
2	3600	208-230/460	56C	EE612	\$705	DS-3F	No	1.15	11.9	33	DC56	6.0-5.7/2.9	
	3600	208-230/460	56C	D2S1AHC	\$710	DS-3F	Rigid	1.15	11.9	33	DC56	6.0-5.4/2.7	FL
	3600	208-230/460	56J	EE733	\$710	DS-3F	No	1.20	12.4	30	DC56	6.6-6.4/3.2	03
	3600	208-230/460	56J	EE733B	\$715	DS-3F	Rigid	1.20	12.4	30	DC56	6.6-6.4/3.2	03
	3600	575	56J	EE733-5	\$719	DS-3F	Remov.	1.20	12.4	30	DC56	2.6	
	1800	208-230/460	56C	D2S2ACR	\$541	DS-3F	No	1.15	13.0	35	DC56	6.1-6.2/3.1	FL
3	3600	208-230/460	56C	EE736	\$775	DS-3F	No	1.15	12.9	35	DC56	9.6-9.4/4.7	
	3600	208-230/460	56J	EE734	\$780	DS-3F	No	1.15	13.4	35	DC56	9.6-9.4/4.7	
	3600	208-230/460	56J	EE734B	\$785	DS-3F	Rigid	1.15	13.4	35	DC56	9.6-9.4/4.7	
	3600	575	56J	EE734-5	\$790	DS-3F	Remov.	1.15	13.4	35	DC56	3.4	
5	3600	208-230/460	182TC	D5P1DC	\$975	DS-3E	Rigid	1.15	16	50	969957	15.7-14.7	03, FL
	1800	208-230/460	184TC	D5P2DC	\$1,008	DS-3E	Rigid	1.15	16.0	60	969574	13.8-13/6.5	03, FL
7-1/2	3600	208-230/460	184TC	D7P1DC	\$1,467	DS-3E	Rigid	1.15	16.0	60	969574	20.3-18.1/9.1	03, FL
	1800	208-230/460	213TC	D7P2DC	\$1,410	DS-3E	Rigid	1.15	17.0	100	969575	20.2-18.5/9.3	03, FL
10	3600	208-230/460	213TC	D10P1DC	\$1,649	DS-3E	Rigid	1.15	18.0	100	969575	27.1-24.3/12.2	03, FL
	1800	208-230/460	215TC	D10P2DC	\$1,677	DS-3E	Rigid	1.15	18.0	110	969575	26.3-23.8/11.9	03, FL
15	3600	208-230/460	215TC	D15P1DC	\$2,287	DS-3E	Rigid	1.15	18.0	110	969575	40-36/18	03, FL

Note 02 Suitable for Wye-Delta start on voltages shown
 Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate

Note 26 Does not include World Motor[®] features
 Note FL All Listed Amps are Full Load Amps

† All marks shown within this document are properties of their respective owners



Special Application Commercial Pump Three Phase Open Dripproof (ODP) C-Face



HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	Base (Feet)	SF	"C" Dim (in.)	Ship Wt.	Dripcover Kit	Max. Amps	Notes
20	3600	208-230/460	254TC	D20P1DC	\$2,707	DS-3E	Rigid	1.15	23.0	160	472131	52-47/23.4	02, 03, FL
	1800	208-230/460	256TC	D20P2DC	\$2,921	DS-3E	Rigid	1.15	24.0	170	472131	54-49/24.4	02, 03, FL
25	3600	208-230/460	256TC	D25P1DC	\$3,219	DS-3E	Rigid	1.15	24.0	170	472131	63-57/28.7	02, 03, FL
	1800	208-230/460	284TC	D25P2DC	\$3,638	DS-3E	Rigid	1.15	25.0	315	969578	64-58/29	02, 03, FL
30	1800	208-230/460	286TC	D30P2DC	\$3,935	DS-3E	Rigid	1.15	25.0	350	969578	77-69/34	02, 03, FL
40	3600	208-230/460	286TSC	D40P1DSC	\$4,912	DS-3E	Rigid	1.15	23.5	350	969578	100-90/45	02, 03, FL
	1800	208-230/460	324TC	D40P2DC	\$5,175	DS-3E	Rigid	1.15	27.3	385	969579	102-91/46	02, 03, FL
50	3600	208-230/460	324TSC	D50P1DSC	\$5,466	DS-3E	Rigid	1.15	25.8	385	969579	130-117/59	02, 03, FL
	1800	208-230/460	326TC	D50P2DC	\$5,684	DS-3E	Rigid	1.15	27.3	415	969579	126-113/56	02, 03, FL
60	3600	208-230/460	326TSC	D60P1DSC	\$6,788	DS-3E	Rigid	1.15	25.8	415	969579	152-136/68	02, 03, FL

Note 02 Suitable for Wye-Delta start on voltages shown
 Note FL All Listed Amps are Full Load Amps

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on Nameplate