

# Special Application Commercial Gate Single Phase, Permanent Split Capacitor Open Dripproof (ODP)



## APPLICATIONS:

For gate openers, hoists and most medium start reversing applications.

## FEATURES:

- 40°C Ambient
- 1.0 Service Factor
- Reversible Rotation
- 115 Volt, 60 Hertz
- Permanent Lubricated Ball Bearings
- 3 Lead Connection
- Manual Reset Thermal Overload Protector
- Terminal Board Connections Without Motor Switch
- Lower Inrush And Operating Currents
- Modest Starting Torque
- Allows Frequent Starts
- Continuous Duty Capacitor
- Continuous Duty/Intermittent Duty (1 HP Intermittent)

## Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	1800	115	56	D12ARM2N	\$555	DS-3FMP	1.00	10.4	19	5.0-5.7	

## Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1800	115	56	D13ARM2N9	\$524	DS-3FMP	1.00	10.8	19	3.9-4.2	
1/2	1800	115	56	D12ARM2N9	\$587	DS-3FMP	1.00	10.8	18	5.0-5.7	

# Special Application Commercial Door Three Phase Totally Enclosed Fan Cooled (TEFC) Rigid Base



## APPLICATIONS:

For commercial door openers and most medium start reversing applications.

## FEATURES:

- 40°C Ambient
- 1.0 Service Factor
- Rigid Base
- Reversible Rotation
- 208/230-460 Volt, 60 Hertz
- Permanent Lubricated Ball Bearings
- Continuous Duty
- Class B Insulation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	1800	208-230/460	56	T12SR2J	\$276	DS-3F	1.00	12.0	17	2.1-2.2/1.1	
3/4	1800	208-230/460	56	T34SR2J	\$293	DS-3F	1.00	12.0	18	2.4-2.9/1.5	
1	1800	208-230/460	56	T1SR2J	\$310	DS-3F	1.00	11.9	22	3.3-3.3/1.7	