

GENERAL PURPOSE UNIMOUNT
 GENERAL PURPOSE HOSTILE DUTY
 GENERAL PURPOSE CORRO-DUTY
 GENERAL PURPOSE 841 PLUS
 GENERAL PURPOSE e-LINE
 GENERAL PURPOSE OPEN DRIPPROOF
 GENERAL PURPOSE HAZARDOUS LOCATION
 GENERAL PURPOSE AUTOMOTIVE DUTY
 COOLING TOWER DUTY
 HAZARDOUS LOCATION
 C-FACE MOTORS
 VARIABLE FREQUENCY

General Purpose Single Phase Div. 1 Hazardous Location Class I (Group C & D), Class II (Group E, F & G)



CH63, CG63

APPLICATIONS:

For use on air compressors, pumps, conveyors, blowers and general industrial equipment located in hazardous areas.

FEATURES:

- UL[®] Listed & CSA[®] Certified
- Temp Code T3C
- Class B Insulation
- Continuous Duty
- Totally Enclosed Fan Cooled Except Where Noted
- 40°C Ambient Rated
- F1 Assembly

Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230 & 110/220	56	XS14CA2J	\$482	DS-3FMP	1.00	12.5	19	5.1/2.5-2.5 & 5.6/2.8	24, 28
	1200	115/230	56	XS14CA3P	\$706	DS-3FMP	1.00	13.0	22	6.8/3.4	24, 28
1/3	3600	115/208-230	56	XS13CA1J	\$560	DS-3FMP	1.00	13.2	29	8.0/3.6-4.0	24
	1800	115/208-230	56	XS13CA2J	\$512	DS-3FMP	1.00	12.7	30	6.8/3.3-3.4	24
	1200	115/230	56	XS13CA3P	\$912	DS-3FMP	1.00	12.7	31	7.2/3.6	24
1/2	3600	115/208-230	56	XS12CA1J	\$608	DS-3FMP	1.00	13.2	29	8.8/4.1-4.4	24
	1800	115/208-230	56	XS12CA2J	\$563	DS-3FMP	1.00	13.2	31	9.8/4.9-4.9	24
	1200	115/230	56H	XS12CA3P	\$1,053	DS-3FMP	1.00	14.2	40	10.0/5.0	24
3/4	3600	115/208-230	56	XS34CA1J	\$686	DS-3FMP	1.00	13.2	31	10.4/5.3-5.2	24
	1800	115/208-230	56	XS34CA2J	\$630	DS-3FMP	1.00	13.7	35	12.6/6.3-6.3	24
1	3600	115/208-230	56	XS1CA1J	\$608	DS-3FMP	1.00	14.2	39	12.0/6.3-6.0	24
	1800	115/208-230	56H	XS1CA2JH	\$714	DS-3FMP	1.00	14.2	32	14.0/6.9-7.0	24

C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230&110/220	56C	XS14CA2JCR	\$482	DS-3FMP	1.00	11.9	25	5.1/2.5-2.5 & 5.6/2.8	24, 28
1/3	3600	115/208-230	56C	XS13CA1JCR	\$614	DS-3FMP	1.00	13.3	30	8.0/3.6-4.0	24
	1800	115/208-230	56C	XS13CA2JCR	\$537	DS-3FMP	1.00	12.8	30	6.8/3.3-3.4	24
1/2	3600	115/208-230	56C	XS12CA1JCR	\$681	DS-3FMP	1.00	13.3	27	8.8/4.1-4.4	24
	1800	115/208-230	56C	XS12CA2JCR	\$563	DS-3FMP	1.00	13.8	32	9.8/4.9-4.9	24
3/4	3600	115/208-230	56C	XS34CA1JCR	\$728	DS-3FMP	1.00	13.3	32	10.4/5.3-5.2	24
	1800	115/208-230	56C	XS34CA2JCR	\$630	DS-3FMP	1.00	14.3	40	12.6/6.3-6.3	24
1	3600	115/208-230	56C	XS1CA1JCR	\$784	DS-3FMP	1.00	14.3	41	12.0/6.3-6.0	24
	1800	115/208-230	56C	XS1CA2JCR	\$675	DS-3FMP	1.00	14.8	41	14.0/6.9-7.0	24

Note 24 Automatic Reset Thermal Overload Protector

Note 28 TENV Enclosure

† All marks shown within this document are properties of their respective owners.

