

General Purpose Single Phase Open Dripproof (ODP), Resilient Base, Capacitor Start



APPLICATIONS:

For air compressors, pumps, conveyors, blowers and general industrial equipment

FEATURES:

- Class A or B Insulation
- Reversible Rotation
- 40°C Ambient
- 60 Hertz
- Continuous Duty

Single Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6	900	115	48	3700	\$555	DS-3FMP	1.35	8.9	15	4.5	25
1/4	1200	115/208-230	56	6305	\$338	DS-3FMP	1.35	11.3	25	6.4/3.0-3.2	24
1/3	3600	115/208-230	48	D13CA1J49	\$281	DS-3FMP	1.35	9.9	17	6/2.9-3.0	24
	1800	115/208-230	56	D13CA2J9	\$296	DS-3FMP	1.35	9.8	25	8.8/3.9-4.4	24
	1800	115/230	48	4145	\$277	DS-3FMP	1.00	9.4	17	6.8/3.4	25
	1800	115/230&110/220	48	6300	\$250	DS-3FMP	1.35	9.9	21	6.5/3.3&7.3/3.6	25, 98
	1800	115/230&110/220	56	6292	\$303	DS-3FMP	1.35	10.3	22	6.5/3.3&7.3/3.6	25, 98
	1200	115/208-230	56	D13CA3J9	\$420	DS-3FMP	1.35	11.3	27	6.8/3.4-3.4	24
	1200	115/230	56	6306	\$406	DS-3FMP	1.35	10.8	27	7.4/3.7	25
	900	115/230-208	56	3705	\$816	DS-3FMP	1.35	11.8	27	8.0/4.0	
1/2	1800	100-120/200-240	56	6309	\$353	DS-3FMP	1.25	10.8	26	6.3-5.6/3.1-2.8	24, 98
	1800	115/208-230	48	D12C2J49	\$227	DS-3FMP	1.25	9.9	22	10.3/4.8-5.3	25
	1800	115/208-230	48	D12CA2J49	\$264	DS-3FMP	1.25	8.7	23	10.3/4.8-5.3	24
	1800	115/208-230	56H	D12CA2JH9	\$303	DS-3FMP	1.25	11.8	27	9.0/4.3-4.5	24
	1800	115/208-230	56	D12C2J9	\$288	DS-3FMP	1.25	11.3	22	9.0/4.3-4.5	25
	1200	115/208-230	56	D12CA3J9	\$548	DS-3FMP	1.25	12.3	28	10.4/5.1-5.2	24
	1200	115/230	56	6310	\$472	DS-3FMP	1.25	10.2	28	10.3/5.2	25
	3/4	3600	115/208-230	56	D34CA1J9	\$272	DS-3FMP	1.25	11.8	26	10.4/5.3-5.2
1800		100-120/200-240	56	6313	\$403	DS-3FMP	1.25	11.3	32	9.2-8.4/4.6-4.2	24, 98
1800		115/230	56	1660	\$314	DS-3FMP	1.00	10.8	27	11.6/5.8	
1800		115/230&110/220	56	4149	\$347	DS-3FMP	1.25	11.3	28	11.3/5.5	98
1800		115-208/230	56H	D34CA2JH9	\$347	DS-3FMP	1.25	11.8	27	11.4/5.7-5.7	24
1800		115-208/230	56	D34C2J9	\$327	DS-3FMP	1.25	11.8	95	11.4/5.7-5.7	25
1200		115/208-230	56H	D34CA3J9	\$655	DS-3FMP	1.15	13.3	40	10.6/5.4-5.3	24
1		3600	115/208-230	56	D1C1J9	\$380	DS-3FMP	1.25	11.8	31	14.6/6.9-7.3
	3600	115/208-230	56	D1CA1J9	\$384	DS-3FMP	1.25	11.8	25	14.6/6.9-7.3	24
	1800	100-120/200-240	56	6317	\$499	DS-3FMP	1.15	12.8	38	12.3-10.8/6.2	24
	1800	115/208-230	56H	D1C2JH9	\$389	DS-3FMP	1.15	12.3	32	14.8/7.5-7.3	25
	1800	115/208-230	56H	D1CA2JH9	\$515	DS-3FMP	1.15	12.3	31	14.8/7.5-7.3	25
	1800	115/208-230	56	3754	\$383	DS-3FMP	1.15	11.8	34	16.4/8.2	
	1200	115/208-230	56H	D1CA3JH9	\$703	DS-3FMP	1.15	13.8	42	12.6/6.4-6.3	24
	1-1/2	3600	115/208-230	56H	D32CA1JH9	\$510	DS-3FMP	1.15	12.31	39	18.6/9.8-9.3
1800		115/208-230	145T	D32C2J149	\$566	DS-3SP	1.15	13.7	45	19.2/10.0-9.6	25
1800		115/208-230	56H	D32CA2JH9	\$630	DS-3FMP	1.15	13.3	38	19.2/10.0-9.6	24
1800		115/230	56	6296	\$551	DS-3FMP	1.00	12.8	41	20.0/10.0	25

Two Speed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
3/4-1/4	1800/1200	115	56	6311	\$448	DS-3FMP	1.25	10.8	26	8.9/6.1	25
1-1/3	1800/1200	208/230	56	6316	\$501	DS-3FMP	1.15	11.8	32	7.4-7.4/4.0-4.3	25

Note 24 Automatic Reset Thermal Overload Protector
Note 25 Non-protected

Note 98 50/60 Hz Motor

