

General Purpose Single Phase Totally Enclosed Fan Cooled (TEFC) Split Phase



RIGID BASE

APPLICATIONS:

For commercial fans and blowers, tools, conveyors, pumps and general industrial equipment requiring moderate starting torque.

FEATURES:

- 40°C Ambient
- 60 Hz
- Continuous Duty
- Class A or B Insulation
- Ball Bearing

Single Speed, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6	1800	115	48	T16B2N49	\$226	DS-3FMP	1.0	10.7	18	3.4	20, 25
1/4	1800	115	48	T14B2N49	\$222	DS-3FMP	1.0	10.7	18	4.4	20, 25
	1200	115/230	56	T14B3P9	\$360	DS-3FMP	1.0	11.9	23	6.7/3.35	20, 25

Single Speed, Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	3600	115	48	T13B1N4	\$236	DS-3FMP	1.0	10.7	15	5.4	25

Note 20 Stud Extensions in 3 5/8" Square Pattern

Note 25 Non-protected

