

# General Purpose Three Phase Open Dripproof (ODP) Energy Efficient, Resilient Base

## APPLICATIONS:

For use on pumps, fans, compressors, material handling and other general purpose applications where contaminants are minimal.

## FEATURES:

- Rolled Steel Frame
- Aluminum End Shields
- 40°C Ambient
- F1 Assembly Position
- Motors Do Not Include World Motor® Features

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1800	208-230/460	56	D13S2A9	\$327	DS-3F	1.35	11.8	20	1.4-1.4/0.7	
1/2	1800	208-230/460	56	D12S2A9	\$325	DS-3F	1.25	11.9	22	1.98-1.9/98	
3/4	1800	208-230/460	56	D34S2A9	\$345	DS-3F	1.25	12.3	23	2.8-2.7/1.4	
1	1800	208-230/460	56H	D1S2AH9	\$394	DS-3F	1.25	12.8	27	3.2-3.0/1.5	
1 1/2	3600	208-230/460	56H	D32SA1AH9	\$541	DS-3F	1.15	12.8	26	4.7-4.4/2.2	
	1800	208-230/460	56H	D32S2AH9	\$412	DS-3F	1.25	12.8	29	4.9-5.0/2.5	

# General Purpose Three Phase Open Dripproof (ODP) Energy Efficient, C-Face



D, R,  
FD, FR

## APPLICATIONS:

For use on pumps, fans, compressors, material handling and other general purpose applications where contaminants are minimal.

## FEATURES:

- World Motor® Features Except Where Noted
- Rolled Steel Frame
- Aluminum End Shields
- 40°C Ambient, NEMA® Design B Performance On 60 Hz Sine Wave Power
- Full HP @ 50 Hz
- Double Shielded Bearings
- F1 Assembly Position

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	Mounting	SF	Length	Ship Wgt.	Full Load Amps	Notes
3/4	3600	208-230/460	56C	EE508	\$444	DS-3F	Footless	1.50	11.3	25	2.7-2.8/1.4	03
	1800	208-230/460	56C	D34S2ACR	\$366	DS-3F	Footless	1.25	11.4	22	2.8-2.7/1.4	
	1200	208-230/460	56C	D34S3DCR	\$704	DS-3F	Footless	1.15	12.0	30	3.4-3.5/1.7	26
1	3600	208-230/460	56C	EE511	\$464	DS-3F	Footless	1.40	11.6	26	3.5-3.4/1.7	03
	3600	208-230/460	56C	EE511B	\$469	DS-3F	Footed	1.40	11.1	26	3.5-3.4/1.7	03
	1800	208-230/460	56HC	D1S2AHC	\$353	DS-3F	Footed	1.25	12.0	28	3.2-3.0/1.5	
1-1/2	3600	208-230/460	56C	EE609	\$537	DS-3F	Footless	1.30	11.4	27	4.4-4.3/2.2	03
	3600	208-230/460	56C	D32S1AHC	\$541	DS-3F	Footed	1.15	11.9	27	4.7-4.4/2.2	26
	1800	208-230/460	56C	D32S2ACR	\$482	DS-3F	Footless	1.25	12.4	32	4.9-5.0/2.5	03
2	3600	208-230/460	56C	EE612	\$705	DS-3F	Footless	1.20	11.9	33	5.5-5.1/2.5	
	3600	208-230/460	56C	D2S1AHC	\$710	DS-3F	Footed	1.15	11.9	33	6.0-5.4/2.7	
	1800	208-230/460	56C	EE708	\$705	DS-3F	Footless	1.15	13.1	38	6.2-5.8/2.9	
3	3600	208-230/460	56C	EE736	\$775	DS-3F	Footless	1.15	12.9	35	7.9-7.6/3.8	

Note 03 60/50 Hz rated with no derate on HP; 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz, 460V 60 Hz ratings operate on 380V 50 Hz; Full 60 & 50 Hz data on nameplate

Note 26 Does not include World Motor® features

† All marks shown within this document are properties of their respective owners.