


Permanent Split Capacitor Ventilation Direct Drive Blower

5.6" & 6.3" Diameter, Totally Enclosed, Air Over (TEAO)




APPLICATIONS:

Design to meet manufacturer's requirements for direct drive ventilation units requiring a totally enclosed motor.

FEATURES:

- Continuous Duty
- 1/2" Dia. x 2 1/2" Shaft
- Reversible Rotation
- Studs For Mounting Fan Guard
- Terminal Board With Side Conduit Plug
- Automatic Thermal Protection
- Includes Capacitor Mounted With Cover
- **Discount Symbol: DS-3HAC**



HP	RPM/Spd.	Volts	Catalog Number	List	NEMA Frame	Amps	Eff.	SF	Bearings	Insul. Class	Total C	Ship Wgt.	Notes	OEM
1/4	1020	115	4153	\$224	48Y	4.5	Std	1.0	Slv	B	10.0	8.5		MQ
	1075/2	115	4812	\$227	48Z	3.3	Std	1.0	Slv	A	9.9	18		
	1075	115	4814	\$219	48Z	3.4	High	1.0	Ball	B	9.9	15		
	1725	115	6326	\$246	56Z	5.0	Std	1.0	Ball	A	9.8	18	94	
1/3	1075	115	4815	\$208	48Z	4.6	High	1.0	Slv	A	10.5	18		
	1725	115	8511	\$209	48Z	5.2	Std	1.0	Ball	B	10.2	15	94	
	1725	115	6328	\$301	56Z	5.4	Std	1.0	Ball	A	9.8	21	94	
1/2	1075	115	4816	\$230	48Z	7.0	High	1.0	Slv	B	10.9	2		
	1725	115	6330	\$318	56Z	7.4	Std	1.0	Ball	A	10.3	23	94	
	1700	115/230	1850	\$295	48Z	5.0/2.5	High	1.0	Ball	B	10.9	25		

MQ = McQuay

Note 94 Split Phase

† All marks shown within this document are properties of their respective owners