RESCUE® Motors Permanent Split Capacitor Condenser Fan 5.6" Diameter, Totally Enclosed, Air Over (TEAO)



RESCUE® Condenser Motors available in 158°F (70°C) ambient ratings!

APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower applications and a variety of mounting styles.

FEATURES:

- High 158°F (70°C) Or 140°C (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Suitable for Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem®† or Trane®† Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- **Discount Symbol DS-3HAC**

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD @ 208V	Cap. MFD @ 230V	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/3	825	208/230	5464	$182	140°F (60°C)	High	10	7.5	1.9	5	5.3	10.3	18	H43
1/4						High	10	7.5	1.5					
1/5						Low	10	7.5	1.2					
1/6						Low	10	7.5	1.0					
1/3	825	208-230	5464H	$186	158°C (70°C)	High	10	7.5	1.9	5	5.3	10.3	18	H43
1/4						High	10	7.5	1.5					
1/5						Low	10	7.5	1.2					
1/6						Low	10	7.5	1.0					
1/3	1075	208/230	5462	$140	140°F (60°C)	High	7.5	5	2.6	5	4.6	9.6	15	H43
1/4						High	7.5	5	2.5					
1/5						Low	7.5	5	2.0					
1/6						Low	7.5	5	1.8					
1/3	1075	208-230	5462H	$153	158°C (70°C)	High	7.5	5	2.6	5	4.6	9.6	18.10	H43
1/4						High	7.5	5	2.5					
1/5						Low	7.5	5	2.0					
1/6						Low	7.5	5	1.8					
1/2	1075	208-230	5465	$177	140°F (60°C)	High	12.5	10	3.0	5	5.3	10.3	19	H43
1/3						High	12.5	10	2.2					
1/4						Low	12.5	10	1.6					
1/5						Low	12.5	10	1.3					
1/2	1075	208-230	5465H	$190	158°C (70°C)	High	12.5	10	3.0	5	5.3	10.6	14	H43
1/3						High	12.5	10	2.2					
1/4						Low	12.5	10	1.6					
1/5						Low	12.5	10	1.3					
3/4	1075	208-230	5482H	$205	158°C (70°C)	High	15	15	4	5	6.3	11.9	14	H43
1/2						High	15	15	2.8					
1/3						Low	15	15	1.9					
1/4						Low	15	15	1.4					

460 Volt RESCUE® Condenser Fan Motors

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/2	1075	460	5480H	$240	158°C (70°C)	High	10	1.3	5	5.6	11.1	19	H43
1/3						High	10	0.9					
1/4						Low	10	0.7					
1/5						Low	10	0.5					
1/6						Low	10	0.5					
3/4	1075	460	5481H	$260	158°C (70°C)	High	15	2.2	5	6.3	11.9	22.38	H43
1/2						High	15	1.3					
1/3						Low	15	1.1					
1/4						Low	15	0.7					

Note H43 Side Shell & Lead End Mounting Screws Included In Carton

† All marks shown within this document are properties of their respective owners.