

Definite Purpose Three Phase Totally Enclosed Fan Cooled (TEFC) Hostile Duty, Inverter Duty 10:1 (6-60 Hz) Speed Range Variable Torque



CTI

APPLICATIONS:

For pumps, fans, blowers or other inverter powered applications having variable torque requirements.

FEATURES:

- Inverter Grade® Insulation System (Meets NEMA® MG-1 Part 31)
- Class F Thermostats (One Per Phase)
- Cast Iron Frame (140: Rolled Steel), Cast Iron End Brackets
- Corrosion Resistant Mill & Chemical Duty Paint
- Stainless Steel Nameplate & Zinc Plated Hardware
- Shaft Slinger On Pulley End For IP54 Protection
- 40°C Ambient, NEMA® Design B Performance On 60 Hertz Sine Wave Power
- Special Balance
- Regreasable Bearings 250 Frame & Up
- Double Shielded Bearings 140-360, Open On 400-440
- Double Dip & Bake With Extra Bracing
- Premium Efficient Design, F1 Assembly Position
- Class F Insulation, 1.15 S.F. On Sine Wave / 1.0 S.F. On PWM
- Constant Horsepower To 90 Hz
- 1.15 S.F. On Sine Wave / 1.0 S.F. On PWM
- Conversion Kits: All Cast Iron Upgrade, C&D Flanges, Drip Cover Kits (except 320-360), See Pages 260-264
- For VFD Guidelines, Refer to Page vii

5:1 (12-60 Hz) Speed Range Constant Torque

HP	RPM (Max Speed)	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	1800 (3600)	230/460	143TC	H1V2BC	\$818	DS-VFM	12.6	65	85.5	2.9/1.5	
	1200 (2400)	230/460	145TC	H1V3BC	\$1,026	DS-VFM	12.6	70	81.5	3.7/1.9	
1-1/2	3600 (7200)	230/460	143TC	H32V1BC	\$842	DS-VFM	12.6	65	84.0	3.9/1.9	
	1800 (3600)	230/460	145TC	H32V2BC	\$906	DS-VFM	12.6	70	85.5	4.4/2.2	
	1200 (2400)	230/460	182TC	H32V3BC	\$1,073	DS-VFM	14.6	100	86.5	5/2.5	
2	3600 (7200)	230/460	145TC	H2V1BC	\$982	DS-VFM	12.6	70	86.5	4.9/2.4	
	1800 (3600)	230/460	145TC	H2V2BC	\$982	DS-VFM	12.6	70	85.5	5.5/2.8	
	1200 (2400)	230/460	184TC	H2V3BC	\$1,190	DS-VFM	15.6	110	87.5	6/3	
3	3600 (7200)	230/460	182TC	H3V1BC	\$1,132	DS-VFM	14.6	100	87.5	7.8/3.9	
	1800 (3600)	230/460	182TC	H3V2BC	\$1,113	DS-VFM	14.6	100	89.5	7.9/4.0	
	1200 (2400)	230/460	213TC	H3V3BC	\$1,572	DS-VFM	17.7	160	90.2	8.7/4.4	
5	3600 (7200)	230/460	184TC	H5V1BC	\$1,401	DS-VFM	15.6	110	88.5	12.2/6.1	
	1800 (3600)	230/460	184TC	H5V2BC	\$1,269	DS-VFM	15.6	110	89.5	12.5/6.3	
	1200 (2400)	230/460	215TC	H5V3BC	\$2,308	DS-VFM	19.2	175	90.2	14/7	
7-1/2	3600 (7200)	230/460	213T	H7V1B	\$1,816	DS-VFM	17.6	160	91.0	17.8/8.9	
	1800 (3600)	230/460	213T	H7V2B	\$1,816	DS-VFM	17.6	160	91.0	18.4/9.2	
	1200 (2400)	230/460	254T	H7V3B	\$3,091	DS-VFM	23.8	300	91.0	18.6/9.3	
10	3600 (7200)	230/460	215T	H10V1B	\$2,144	DS-VFM	19.1	175	91.0	23.2/11.6	
	1800 (3600)	230/460	215T	H10V2B	\$2,191	DS-VFM	19.1	175	91.7	23.8/11.9	
	1200 (2400)	230/460	256T	H10V3B	\$3,630	DS-VFM	25.5	340	91.7	24.5/12.3	
15	3600 (7200)	230/460	254T	H15V1B	\$2,914	DS-VFM	23.8	300	90.2	35/17.7	
	1800 (3600)	230/460	254T	H15V2B	\$3,040	DS-VFM	23.8	300	92.4	37/18.4	
	1200 (2400)	230/460	284T	H15V3B	\$4,481	DS-VFM	25.5	380	91.7	37/18.7	
20	3600 (7200)	230/460	256T	H20V1B	\$3,486	DS-VFM	25.5	350	91.0	46/23	
	1800 (3600)	230/460	256T	H20V2B	\$3,499	DS-VFM	25.5	360	93.0	47/23.7	
	1200 (2400)	230/460	286T	H20V3B	\$5,448	DS-VFM	27.0	410	91.7	49/24.5	
25	3600 (5400)	230/460	284TS	H25V1BS	\$4,350	DS-VFM	24.8	350	91.7	59/29.3	
	1800 (2700)	230/460	284T	H25V2B	\$4,256	DS-VFM	25.5	380	93.0	59/29.4	
	1200 (2400)	230/460	324T	H25V3B	\$6,615	DS-VFM	30.6	600	92.4	59/29.5	
30	3600 (5400)	230/460	286TS	H30V1BS	\$5,140	DS-VFM	26.3	400	91.7	69/35	
	1800 (2700)	230/460	286T	H30V2B	\$5,036	DS-VFM	27.0	440	93.6	69/34	
	1200 (2400)	230/460	326T	H30V3B	\$7,580	DS-VFM	30.6	675	93.0	70/35	

† All marks shown within this document are properties of their respective owners

Definite Purpose Three Phase Totally Enclosed Fan Cooled (TEFC) Hostile Duty, Inverter Duty 10:1 (6-60 Hz) Speed Range Variable Torque



CTI

5:1 (12-60 Hz) Speed Range Constant Torque

HP	RPM (Max Speed)	Voltage	Frame	Catalog Number	List	Discount Symbol	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
40	3600 (5400)	230/460	324TS	H40V1BS	\$6,247	DS-VFM	29.1	560	92.4	91/46	
	1800 (2700)	230/460	324T	H40V2B	\$6,059	DS-VFM	30.6	600	93.6	92/46	
	1200 (2400)	230/460	364T	H40V3B	\$10,759	DS-VFM	32.6	875	94.1	93/46	
50	3600 (5400)	230/460	326TS	H50V1BS	\$8,040	DS-VFM	29.1	600	93.0	112/56	
	1800 (2700)	230/460	326T	H50V2B	\$7,460	DS-VFM	30.6	610	94.1	113/56	
	1200 (2400)	230/460	365T	H50V3B	\$12,029	DS-VFM	32.6	900	94.1	116/58	
60	3600 (4500)	230/460	364TS	H60V1BS	\$10,492	DS-VFM	30.4	790	93.0	136/68	
	1800 (3600)	230/460	364T	H60V2B	\$10,631	DS-VFM	32.6	825	94.5	136/68	
	1200 (2400)	230/460	404T	H60V3B	\$13,624	DS-VFM	37.6	1160	94.5	140/70	
75	3600 (4500)	230/460	365TS	H75V1BS	\$13,209	DS-VFM	30.4	830	93.6	167/83	
	1800 (3600)	230/460	365T	H75V2B	\$13,699	DS-VFM	32.5	910	95.0	168/84	
	1200 (2400)	230/460	405T	H75V3B	\$16,291	DS-VFM	37.6	1300	95.0	172/86	
100	3600 (4500)	230/460	405TS	H100V1BS	\$16,890	DS-VFM	34.6	1200	94.5	218/109	
	1800 (3600)	230/460	405T	H100V2B	\$16,081	DS-VFM	37.6	1250	95.4	226/113	
	1200 (2400)	460	444T	H100V3C	\$22,804	DS-VFM	43.4	1660	94.5	124	
125	3600 (4500)	460	444TS	H125V1CS	\$24,360	DS-VFM	39.6	1550	94.5	147	
	1800 (3600)	460	444T	H125V2C	\$22,627	DS-VFM	43.4	1675	95.4	146	
	1200 (2400)	460	445T	H125V3C	\$26,245	DS-VFM	45.4	1750	95.4	153	
150	3600 (4500)	460	445TS	H150V1CS	\$29,266	DS-VFM	41.6	1650	95.4	179	
	1800 (3600)	460	445T	H150V2C	\$26,406	DS-VFM	45.4	1780	95.8	171	
	1200 (2400)	460	447T	H150V3C	\$30,644	DS-VFM	48.9	2100	95.0	181	
200	3600 (4500)	460	447TS	H200V1CS	\$37,024	DS-VFM	45.1	2040	95.4	219	
	1800 (3600)	460	447T	H200V2C	\$31,737	DS-VFM	48.9	2120	95.8	226	



GENERAL PURPOSE UNIMOUNT
GENERAL PURPOSE HOSTILE DUTY
GENERAL PURPOSE CORRO-DUTY
GENERAL PURPOSE 841 PLUS
GENERAL PURPOSE e-LINE
GENERAL PURPOSE OPEN DRIPPROOF
GENERAL PURPOSE HAZARDOUS LOCATION
GENERAL PURPOSE AUTOMOTIVE DUTY
COOLING TOWER DUTY
HAZARDOUS LOCATION
C-FACE MOTORS
VARIABLE FREQUENCY