

56 Frame Thru-Bolt Pool & Spa Motors

6.5" Diameter, Single and Two Speed



FEATURES:

- Open Dripproof
- Class B Temperature Rise
- Rigid Base
- Premium Energy Efficient Design
- Thru Bolt Mount
- 1081 & 1563 Design
- Shaft Thread 3/8-16 UNC-2A
- Thermally Protected
- 3 o'clock Conduit
- Class F Insulated
- Sealed Ball Bearing
- 60°C Ambient
- **Discount Symbol: DS-FPS**



Premium Energy Efficient, Single Speed, Switchless Design

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List Price	Motor Frame	Length Less Shaft	Ship Wgt.	Notes
1-1/2	1.0	3450	230/115	60	8.8/17.5	TS602	\$300	56Y	9.58	28	1
2	1.0	3450	230	60	10.0	TS603	\$330	56Y	9.58	31	
2-1/2	1.0	3450	230	60	11.0	TS604	\$390	56Y	9.58	32	
3	1.0	3450	230	60	12.0	TS605	\$454	56Y	10.08	35	
4	1.0	3450	230	60	16.4	TS606	\$518	56Y	10.58	39	
5	1.0	3450	230	60	19.5	TS607	\$595	56Y	12.58	50	



Premium Energy Efficient, Two Speed, Soft Start (Switch Design)

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List Price	Motor Frame	Length Less Shaft	Ship Wgt.	Notes
1-1/2 / .18	1.0	3450/1725	230	60	8.0/3.0	*TT502	\$329	56Y	9.58	31	
2 / .25	1.0	3450/1725	230	60	10.0/3.5	*TT503	\$409	56Y	10.08	35	
2-1/2 / .33	1.0	3450/1725	230	60	11.0/3.8	*TT504	\$455	56Y	10.33	36	
3 / .38	1.0	3450/1725	230	60	12.0/4.4	*TT505	\$504	56Y	10.83	41	
4 / .50	1.0	3450/1725	230	60	16.4/4.8	*TT506	\$595	56Y	11.58	45	
5 / .63	1.0	3450/1725	230	60	19.5/5.0	*TT507	\$640	56Y	12.08	48	



Extreme E® represents our most efficient running, highest performing lines of motors.

Note 1

Capacitor start design

*Meets California Energy Commission Appliance Regulations 2008 (Publication Number CEC-400-2006-002-REV1)

