

# Painted Washdown, Single Phase, Totally Enclosed C-Face

All Ratings Are Compliant with Energy Independence and Security Act (EISA) Standards



The Slicker™

## APPLICATIONS:

Suitable for food processors, canners, meat packers, bakeries, dairies, drug and cosmetic manufacturers for sanitary, easily cleaned motors.

## FEATURES:

- Class F Insulation
- BISSC® Certified, Smooth Design For Easy Cleaning
- USDA® Approved Non-Toxic White Epoxy Paint
- V-Ring Rotating Lip Seal On Shaft End
- F1 Assembly Position
- Double Contact Sealed Ball Bearings
- Reversible Rotation
- Internal Corrosion Protection On Rotor, Stator, Winding & Frame
- Stationary Grease Seal On Both Ends
- 303 Stainless Steel Shaft
- Moisture-Resistant Gasketed Conduit Box With NPT Lead Holes
- Totally Enclosed Fan Cooled (TEFC) Except Where Noted
- Multiple Stainless Steel T-type Drains
- Automatic Reset Thermal Overload Protector on Yoke Mount Fan Motors

## Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	3600	115/208-230	56C	WD12C1JC	\$523	DS-3SP	1.15	11.8	32	7.3/3.9-3.7	28
	1800	115/208-230	56C	WD12C2JC	\$537	DS-3SP	1.15	12.8	28	9.5/4.6-4.8	25
3/4	3600	115/208-230	56C	WD34C1JC	\$538	DS-3SP	1.15	12.3	40	9.7/5.3-4.9	28
	1800	115/208-230	56C	WD34C2JC	\$611	DS-3SP	1.15	11.6	33	12.8/6.4-6.5	
1	3600	115/208-230	56C	WD1C1JC	\$583	DS-3SP	1.15	13.3	35	13.6/6.9-6.8	
	1800	115/208-230	56HC	WD1C2JHC	\$702	DS-3SP	1.15	12.6	64	15.4/7.8-7.6	
1-1/2	3600	115/208-230	56HC	WD32C1JHC	\$768	DS-3SP	1.15	13.8	41	14.6/8.1-7.4	CSCR
	1800	115/208-230	56HC	WD32C2JHC	\$896	DS-3SP	1.15	13.6	51	14.4/8.0-7.2	CSCR
2	1800	115/230	56HC	WD2C2PHC	\$1,052	DS-3SP	1.15	15.3	53	19.6/9.8	CSCR

## Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	3600	115/208-230	56C	WD12C1JCR	\$576	DS-3SP	1.15	12.8	31	7.3/3.9-3.7	28
	1800	115/208-230	56C	WD12C2JCR	\$663	DS-3SP	1.15	12.8	41	8.8/4.3-4.4	28
3/4	1800	115/208-230	56C	WD34C2JCR	\$748	DS-3SP	1.15	13.8	50	7.8/4.3-3.9	28, CSCR
1	3600	115/208-230	56C	WD1C1JCR	\$672	DS-3SP	1.15	13.8	51	9.9/5.8-5.3	28, CSCR
	1800	115/208-230	56C	WD1C2JCR	\$848	DS-3SP	1.00	14.3	51	10.3/5.5-5.2	CSCR
2	1800	115/230	56C	WD2C2JCR	\$1,059	DS-3SP	1.15	15.3	82	19.6/9.8	CSCR

## Permanent Split Capacitor, Yoke Mount, Non-Oscillating Totally Enclosed Air Over (TEAO) Fan Motors

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/230	56YZ	WD14AA2PZ7	\$426	DS-3FMP	1.00	10.9	22	3.5/1.7	24
1/3	1800	115/230	56YZ	WD13AA2PZ7	\$448	DS-3FMP	1.00	10.9	24	4.9/2.5	24
1/2	1800	115/230	56YZ	WD12AA2PZ7	\$481	DS-3FMP	1.00	11.9	26	5.9/2.9	24

Note 24 Automatic Reset Thermal Overload Protector  
Note 25 Non-protected

Note 28 TENV Enclosure  
Note CSCR Capacitor Start Capacitor Run

† All marks shown within this document are properties of their respective owners.