

All Stainless Steel Washdown, Three Phase, Totally Enclosed, C-Face

All Ratings Are Compliant with Energy Independence and Security Act (EISA) Standards



The Silver Bullet

APPLICATIONS:

Suitable for food processors, canners, meat packers, bakeries, dairies, drug and cosmetic manufacturers for sanitary, easily cleaned motors.

FEATURES:

- All Stainless Steel External Construction
- 40°C Ambient, NEMA® Design B
- Inverter Grade® Insulation System (Meets NEMA® MG-1 Part 31)
- 303 Stainless Steel Shaft
- Multiple Stainless Steel T-type Drains
- Totally Enclosed Fan Cooled (TEFC) Except Where Noted
- Rust Inhibitor on Rotor
- BISSC® Certified
- VBX® Bearing Isolators by Inpro/Seal On Drive End
- Double Sealed Ball Bearings
- Laser-Etched Oversized Nameplate
- RTV-Sealed Lead Exit Holes
- Moisture Resistant Gasketed Conduit Box with NPT Lead Holes
- Easy to Read Connection Leads

Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	1800	208-230/460	56HC	WDS12S2AHC	\$1,435	DS-3PF	1.15	11.9	34	78.5	1.8-1.9/1	28
3/4	1800	208-230/460	56HC	WDS34S2AHC	\$1,484	DS-3PF	1.15	11.9	38	82.5	2.4-2.4/1.2	28
1	1800	208-230/460	143TC	WDS1E2AC	\$1,525	DS-3PF	1.15	11.9	39	85.5	3.1-2.9/1.4	28
	1800	208-230/460	56HC	WDS1S2AHC	\$1,525	DS-3PF	1.15	11.9	39	85.5	3.1-2.9/1.4	28
1-1/2	1800	208-230/460	145TC	WDS32P2AC	\$2,032	DS-3PF	1.15	13.2	37	86.5	4.3-4.1/2.1	
2	1800	208-230/460	145TC	WDS2P2AC	\$2,145	DS-3PF	1.15	13.2	37	86.5	5.7-5.4/2.7	

Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	1800	208-230/460	56C	WDS12S2ACR	\$1,403	DS-3PF	1.15	11.9	34	78.5	1.8-1.9/1	28
3/4	1800	208-230/460	56C	WDS34S2ACR	\$1,444	DS-3PF	1.15	11.9	38	82.5	2.4-2.4/1.2	28
1	1800	208-230/460	143TC	WDS1S2ACR	\$1,492	DS-3PF	1.15	11.9	39	85.5	3.1-2.9/1.4	28
	1800	208-230/460	56C	WDS1S2AFCR	\$1,492	DS-3PF	1.15	11.9	39	85.5	3.1-2.9/1.4	28
1-1/2	1800	208-230/460	145TC	WDS32P2ACR	\$1,989	DS-3PF	1.15	13.2	37	86.5	4.3-4.1/2.1	
	1800	208-230/460	56C	WDS32S2AFCR	\$1,525	DS-3PF	1.15	13.2	46	86.5	4.3-4.1/2.1	
2	1800	208-230/460	145TC	WDS2P2ACR	\$2,102	DS-3PF	1.15	13.2	37	86.5	5.7-5.4/2.7	
	1800	208-230/460	56C	WDS2S2AFCR	\$1,854	DS-3PF	1.15	13.2	49	86.5	5.7-5.4/2.7	



Note 28 TENV Enclosure

† All marks shown within this document are properties of their respective owners.