

# Paint Free Washdown, Three Phase, Totally Enclosed, C-Face

All Ratings Are Compliant with Energy Independence and Security Act (EISA) Standards



## APPLICATIONS:

Suitable for food processors, canners, meat packers, bakeries, dairies, drug and cosmetic manufacturers for sanitary, easily cleaned motors.

## FEATURES:

- Inverter Grade<sup>®</sup> Insulation System (Meets NEMA<sup>®</sup> MG-1 Part 31)
- BISSC<sup>®†</sup> Certified
- VBX<sup>®†</sup> Bearing Isolators By InproSeal On Drive End (Both Ends On 180-210 Frame)
- 303 Stainless Steel Shaft
- Multiple Stainless T-Type Drains
- Double Contact Sealed Ball Bearings
- Laser-Etched Oversized Nameplate
- Totally Enclosed Fan Cooled (TEFC) Except Where Noted
- RTV-Sealed Lead Exit
- Moisture Resistant Gasketed Conduit Box with NPT Lead Holes
- Stainless Steel Frame
- Easy to Read Connection Leads
- Rust Inhibitor on Rotor
- 40°C Ambient, NEMA<sup>®</sup> Design B

## Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	1800	208-230/460	56HC	WDP12S2AHC	\$774	DS-3PF	1.15	12.2	30	78.5	2.0-1.9/0.9	28
3/4	1800	208-230/460	56HC	WDP34S2AHC	\$895	DS-3PF	1.15	12.2	31	80.0	2.8-2.7/1.3	28
1	1800	208-230/460	145TC	WDP1S2AC	\$926	DS-3PF	1.15	13.8	32	85.5	3.5-3.4/1.7	28
	1800	208-230/460	56HC	WDP1S2AHC	\$926	DS-3PF	1.15	13.7	32	85.5	3.5-3.4/1.7	28
1-1/2	1800	208-230/460	145TC	WDP32S2AC	\$967	DS-3PF	1.00	13.8	33	87.5	4.9-4.8/2.4	28
	1800	208-230/460	56HC	WDP32S2AHC	\$967	DS-3PF	1.00	13.7	33	87.5	4.9-4.8/2.4	28
2	1800	208-230/460	56HC	WDP2S2AHC	\$1,194	DS-3PF	1.15	14.5	44	82.5	7.0-7.0/3.5	
3	1800	208-230/460	182TC	WDP3P2AC	\$1,932	DS-3PF	1.15	18.5	58	89.5	8.3-7.6/3.8	
5	1800	208-230/460	184TC	WDP5P2AC	\$2,132	DS-3PF	1.15	18.5	75	89.5	13.6-12.3/6.1	
7-1/2	1800	208-230/460	213TC	WDP7P2AC	\$2,568	DS-3PF	1.15	21.2	117	91.7	19.9-18.1/9.0	
10	1800	208-230/460	215TC	WDP10P2AC	\$2,737	DS-3PF	1.15	21.2	125	91.7	26.5-23.8/11.9	

## Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	1800	208-230/460	56C	WDP12S2ACR	\$766	DS-3PF	1.15	12.2	36	78.5	2.0-1.9/0.9	28
	1200	208-230/460	56C	WDP12S3DCR	\$784	DS-3PF	1.15	12.3	30	82.5	2.2-2.2/1.1	28
3/4	1800	208-230/460	56C	WDP34S2ACR	\$887	DS-3PF	1.15	12.2	37	80.0	2.8-2.7/1.3	28
1	1800	208-230/460	145TC	WDP1S2ACR	\$918	DS-3PF	1.15	13.8	32	85.5	3.5-3.4/1.7	28
	1800	208-230/460	56C	WDP1S2AFCR	\$918	DS-3PF	1.15	13.7	38	85.5	3.5-3.4/1.7	28
	1200	208-230/460	56C	WDP1S3DCR	\$964	DS-3PF	1.15	13.8	32	85.5	4.7-4.8/2.4	28
1-1/2	1800	208-230/460	145TC	WDP32S2ACR	\$960	DS-3PF	1.00	13.8	33	87.5	4.9-4.8/2.4	28
2	1800	208-230/460	145TC	WDP2E2ACR	\$1,096	DS-3PF	1.15	14.6	44	84.0	7.0-7.0/3.5	
	1800	208-230/460	145TC	WDP2P2ACR	\$1,430	DS-3PF	1.00	14.9	44	86.5	6.2-6.0/3.0	
	1800	208-230/460	56C	WDP2S2AFCR	\$1,096	DS-3PF	1.15	14.5	44	84.0	7.0-7.0/3.5	

Note 28 TENV Enclosure

† All marks shown within this document are properties of their respective owners.