

# Painted Washdown Three Phase, Totally Enclosed

All Ratings Are Compliant with Energy Independence and Security Act (EISA) Standards



The Slicker™

## APPLICATIONS:

Suitable for food processors, canners, meat packers, bakeries, dairies, drug and cosmetic manufacturers for sanitary, easily cleaned motors.

## FEATURES:

- Class F Insulation, Class B Rise At Full Load On 60 Hz. Sine Wave Power
- BISSC® Certified, Smooth Design For Easy Cleaning
- USDA® Approved Non-Toxic White Epoxy Paint
- Moisture Resistant Gasketed Conduit Box With NPT Lead Holes
- V-Ring Rotating Shaft Seals
- Full 50 & 60 Hertz Operating Data On Nameplate (180-210 Frame)
- 40°C Ambient, NEMA® Design B Performance On 60 Hz. Sine Wave Power Except WD3E2D14 (Design C)
- Double Contact Sealed Ball Bearings
- Internal Corrosion Protection On Rotor, Stator, Winding & Frame
- Double Dip & Bake On Winding
- 303 Stainless Steel Shaft, F1 Assembly Position
- Stainless Steel Nameplate
- Totally Enclosed Fan Cooled (TEFC) Except Where Noted
- Multiple Stainless Steel T-Type Drains (56 & 140 Frames)
- Removable Drain Plugs (180 & 210 Frames)

## Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/3	1800	208-230/460	56	WD13S2A	\$440	DS-3F	1.35	10.8	36	-	1.9-1.8/0.9	28
1/2	1800	208-230/460	56	WD12S2A	\$572	DS-3F	1.15	10.8	29	80.0	1.9-1.8/0.9	28
3/4	1800	208-230/460	56	WD34S2A	\$600	DS-3F	1.15	11.8	38	82.5	2.6-2.4/1.2	28
	1200	208-230/460	143T	WD34S3A14	\$744	DS-3F	1.15	13.8	35	78.0	3.1-3.2/1.6	
1	1800	208-230/460	143T	WD1P2A14	\$959	DS-3XE	1.15	14.3	35	85.5	3.3-3.3/1.6	
	1800	208-230/460	56	WD1S2A	\$627	DS-3F	1.15	12.3	40	82.5	3.4-3.3/1.7	28
	1200	208-230/460	145T	WD1P3A	\$945	DS-3XE	1.15	15.8	48	82.5	3.8-3.8/1.9	
1-1/2	1800	208-230/460	145T	WD32P2A14	\$1,069	DS-3XE	1.00	14.8	32	86.5	4.8-4.6/2.3	
	1800	208-230/460	56H	WD32S2AH	\$688	DS-3F	1.00	13.8	52	86.5	4.6-4.4/2.2	28
2	1800	208-230/460	145T	WD2P2A14	\$1,300	DS-3XE	1.00	14.8	26	86.5	6.2-6.0/3.0	
	1800	208-230/460	145T	WD2P2A143	\$1,300	DS-3XE	1.15	14.8	26	86.5	6.2-6.0/3.0	96
3	1800	208-230/460	145T	WD3E2D14	\$1,442	DS-3F	1.00	15.8	26	86.5	9.5-9.2/4.6	96
	1800	208-230/460	182T	WD3P2D	\$1,500	DS-3XE	1.15	15.8	55	89.5	8.2-7.6/3.8	
5	1800	208-230/460	184T	WD5P2D	\$1,564	DS-3XE	1.15	15.8	76	89.5	13.5-12.5/6.2	
7-1/2	1800	208-230/460	213T	WD7P2D	\$2,213	DS-3XE	1.15	18.3	117	91.7	20.0-18.2/9.1	
10	1800	208-230/460	215T	WD10P2D	\$2,394	DS-3XE	1.15	19.3	125	91.7	26.5-23.9/11.9	

## C-Face Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/2	3600	208-230/460	56C	WD12S1AC	\$521	DS-3F	1.15	11.8	31	75.5	1.8-1.6/0.8	28
	1800	208-230/460	56C	WD12S2AC	\$600	DS-3F	1.15	11.3	30	82.5	1.9-1.8/0.9	28
3/4	3600	208-230/460	56C	WD34S1AC	\$588	DS-3F	1.15	11.8	24	75.5	2.1-1.9/0.9	28
	1800	208-230/460	56C	WD34S2AC	\$695	DS-3F	1.15	12.3	38	82.1	2.6-2.4/1.2	28
1	3600	208-230/460	56C	WD1S1AC	\$695	DS-3F	1.15	12.3	38	-	3.4-3.2/1.6	28
	1800	208-230/460	143TC	WD1S2A14C	\$781	DS-3F	1.15	12.8	40	77.4	3.4-3.3/1.7	28
	1800	208-230/460	56C	WD1S2AC	\$725	DS-3F	1.15	12.8	40	-	3.4-3.3/1.7	28
1-1/2	3600	208-230/460	56C	WD32S1AC	\$761	DS-3F	1.15	12.8	46	-	4.3-4.1/2.1	28
	1800	208-230/460	145TC	WD32S2A14C	\$815	DS-3F	1.00	14.3	52	87.5	4.6-4.4/2.2	28
	1800	208-230/460	56HC	WD32S2AHC	\$753	DS-3F	1.00	14.3	52	87.5	4.6-4.4/2.2	28

Note 28 TENV Enclosure

Note 96 Feather Picker Features = F0 Mounting Position

† All marks shown within this document are properties of their respective owners.

# Painted Washdown Three Phase, Totally Enclosed

All Ratings Are Compliant with Energy Independence and Security Act (EISA) Standards



The Slicker™

## C-Face Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
2	3600	208-230/460	145TC	WD2P1A14C	\$780	DS-3XE	1.15	13.9	35	86.5	6.1-5.6/2.8	
	3600	208-230/460	56HC	WD2S1AHC	\$843	DS-3F	1.15	13.3	34	80.0	6.0-5.4/2.7	
	1800	208-230/460	145TC	WD2P2A14C	\$1,206	DS-3XE	1.00	14.9	41	86.5	6.2-6.0/3.0	
	1800	208-230/460	56HC	WD2S2AHC	\$826	DS-3F	1.00	14.4	41	84.0	6.3-6.1/3.1	
3	3600	208-230/460	145TC	WD3P1A14C	\$1,229	DS-3XE	1.15	14.4	46	85.5	8.8-7.3/3.6	14
	1800	208-230/460	182TC	WD3P2DC	\$1,477	DS-3XE	1.15	16.8	58	89.5	8.2-7.6/3.8	
5	1800	208-230/460	184TC	WD5P2DC	\$1,581	DS-3XE	1.15	16.8	87	89.5	13.5-12.5/6.2	
7-1/2	1800	208-230/460	213TC	WD7P2DC	\$1,961	DS-3XE	1.15	19.4	117	91.7	20.0-18.2/9.1	
10	1800	208-230/460	215TC	WD10P2DC	\$2,038	DS-3XE	1.15	20.4	128	91.7	26.5-23.9/11.9	

## C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/3	1800	208-230/460	56C	WD13S2ACR	\$540	DS-3F	1.35	11.3	28	80.0	1.9-1.8/0.9	28
1/2	1800	208-230/460	56C	WD12S2ACR	\$596	DS-3F	1.15	11.3	29	-	1.9-1.8/0.9	28
3/4	1800	208-230/460	56C	WD34S2ACR	\$689	DS-3F	1.15	12.3	37	82.5	2.6-2.4/1.2	28
1	3600	208-230/460	56C	WD1S1ACR	\$590	DS-3F	1.15	12.3	37	-	3.4-3.2/1.6	28
	1800	208-230/460	143TC	WD1S2A14CR	\$722	DS-3F	1.15	12.8	41	77.4	3.4-3.3/1.7	28
	1800	208-230/460	56C	WD1S2ACR	\$722	DS-3F	1.15	12.8	41	82.5	3.4-3.3/1.7	28
1-1/2	3600	208-230/460	56C	WD32S1ACR	\$770	DS-3F	1.15	12.8	45	82.5	4.3-4.1/2.1	28
	1800	208-230/460	145TC	WD32S2A14CR	\$751	DS-3F	1.00	14.4	51	80.0	4.6-4.4/2/2	28
	1800	208-230/460	56C	WD32S2ACR	\$751	DS-3F	1.00	14.4	51	87.5	4.6-4.4/2.2	28
2	3600	208-230/460	56C	WD2S1ACR	\$964	DS-3F	1.15	13.4	34	80.0	6.0-5.4/2.7	
	1800	208-230/460	145TC	WD2E2A14CR	\$857	DS-3F	1.00	14.4	40	84.0	6.0-5.9/3.0	
	1800	208-230/460	145TC	WD2P2A14CR	\$1,287	DS-3XE	1.00	14.9	40	86.5	6.2-6.0/3.0	
	1800	208-230/460	56C	WD2S2ACR	\$857	DS-3F	1.00	14.4	40	84.0	6.3-6.1/3.1	
3	3600	208-230/460	56C	WD3S1ACR	\$1,030	DS-3F	1.15	14.4	47	85.5	8.8-7.3/3.6	
	1800	208-230/460	182TC	WD3E2DCR	\$1,110	DS-3FTE	1.15	16.8	73	87.5	8.5-7.9/3.9	
	1800	208-230/460	182TC	WD3P2DCR	\$1,477	DS-3XE	1.15	16.8	58	89.5	8.2-7.6/3.8	
5	1800	208-230/460	184TC	WD5E2DCR	\$1,256	DS-3FTE	1.15	16.8	89	87.5	14-12.6/6.3	
	1800	208-230/460	184TC	WD5P2DCR	\$1,581	DS-3XE	1.15	16.8	87	89.5	13.5-12.5/6.2	
7-1/2	1800	208-230/460	213TC	WD7E2DCR	\$1,595	DS-3FTE	1.15	19.4	115	91.0	20.1-18.3/9.1	
	1800	208-230/460	213TC	WD7P2DCR	\$1,961	DS-3XE	1.15	19.4	117	91.7	20.0-18.2/9.1	
10	1800	208-230/460	215TC	WD10E2DCR	\$1,766	DS-3FTE	1.15	20.4	125	91.0	26.6-23.8/11.9	
	1800	208-230/460	215TC	WD10P2DCR	\$2,038	DS-3XE	1.15	20.4	128	91.7	26.5-23.9/11.9	

Note 14 NEMA® Design A  
Note 28 TENV Enclosure

† All marks shown within this document are properties of their respective owners.



DRIVES  
BRAKE MOTORS  
GENERAL PURPOSE SINGLE PHASE  
HVAC  
WASHDOWN  
AGRICULTURE  
COMMERCIAL PUMP MOTORS  
CLOSE COUPLED PUMP MOTORS  
FIRE PUMP MOTORS  
POOL & SPA MOTORS  
RESIDENTIAL WATER PUMP  
ELEVATOR AND GATE & DOOR