2EZ SPEED Two Speed with Timer NEW
Switchless Design, 6.5" Frame Diameter, Category “S” & “J”

FEATURES:

- Two Compartment
- Shaft Threads – (Square Flange) 1/2-20 UNC-2A or (C-Flange) 7/16-20 UNF-2A
- 50°C Ambient
- Triple Bearing Protection
- 1081 Design
- Continuous Duty
- Class B Insulated
- Open Drip-Proof
- Sealed Ball Bearings
- Switchless Design
- 300 Series Stainless Steel Shaft
- Thermally Protected
- 6.5" Diameter Frame
- Fully Integrated Motor Control
- Program for Low & High Speeds
- Two Settings – Mon-Fri and Sat/Sun
- High/Low Speed Override
- Freeze Sensor
- California Title 20/24 Compliant

extreme-E Square Flange, Premium Energy Efficient, Full Service Factor, Full Rated, Category “S”

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
3/4 / .12	1.67	3450/1725	230	60	5.8 / 1.2	EB2980T*	56Y	12.05	32
1.0 / .16	1.65	3450/1725	230	60	7.4 / 1.3	EB2982T*	56Y	12.30	34
1.5 / .25	1.47	3450/1725	230	60	9.2 / 2.1	EB2983T*	56Y	12.55	36
2.0 / .33	1.30	3450/1725	230	60	10.6 / 2.4	EB2984T*	56Y	13.30	39

extreme-E C-Flange, Premium Energy Efficient, Full Service Factor, Full Rated, Category “J”

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
3/4 / .10	1.50	3450/1725	230	60	5.6 / 1.2	EB2973HT*	56J	12.27	31
1 / .12	1.40	3450/1725	230	60	6.5 / 1.3	EB2975T*	56J	12.27	33
1.5 / .20	1.30	3450/1725	230	60	8.2 / 2.0	EB2977T*	56J	12.27	35
2 / .25	1.20	3450/1725	230	60	10.0 / 2.1	EB2979T*	56J	12.52	38

*Meets California Energy Commission Appliance Regulations 2008 (Publication Number CEC-400-2006-002-REV1)
Catalog numbers are for competitive comparison purposes only.

extreme-E Extreme-E® represents our most efficient running, highest performing lines of motors.

† All marks shown within this document are properties of their respective owners.