

THRU BOLT POOL AND SPA

6.5" Frame Diameter

Features:

- Open Dripproof
- Thru Bolt Mount
- Class F Insulated
- Class B Temperature Rise
- 1081 & 1563 Design
- Sealed Ball Bearing
- Rigid Base
- Thermally Protected
- 60° C Ambient
- 3 O'clock Conduit
- Premium Energy Efficient Design
- Shaft Thread 3/8-16 UNC-2A



| HP | SF | RPM | VOLT | FREQ | SF AMPS | CATALOG NUMBER | MOTOR FRAME | LENGTH LESS SHAFT | WGT | NOTES |
|---|-----|-----------|---------|------|----------|----------------|-------------|-------------------|-----|-------|
| Premium Energy Efficient Single Speed, Switchless Design | | | | | | | | | | |
| 1.5 | 1.0 | 3450 | 230/115 | 60 | 8.8/17.5 | TS602 | 56Y | 9.58 | 28 | 1 |
| 2.0 | 1.0 | 3450 | 230 | 60 | 10.0 | TS603 | 56Y | 9.58 | 31 | |
| 2.5 | 1.0 | 3450 | 230 | 60 | 11.0 | TS604 | 56Y | 9.58 | 32 | |
| 3.0 | 1.0 | 3450 | 230 | 60 | 12.0 | TS605 | 56Y | 10.08 | 35 | |
| 4.0 | 1.0 | 3450 | 230 | 60 | 16.4 | TS606 | 56Y | 10.58 | 39 | |
| 5.0 | 1.0 | 3450 | 230 | 60 | 19.5 | TS607 | 56Y | 12.58 | 50 | |
| Premium Energy Efficient TWO SPEED Soft Start | | | | | | | | | | |
| 1.5/.18 | 1.0 | 3450/1725 | 230 | 60 | 8.0/3.0 | *TT502 | 56Y | 9.58 | 31 | |
| 2.0/.25 | 1.0 | 3450/1725 | 230 | 60 | 10.0/3.5 | *TT503 | 56Y | 10.08 | 35 | |
| 2.5/.33 | 1.0 | 3450/1725 | 230 | 60 | 11.0/3.8 | *TT504 | 56Y | 10.33 | 36 | |
| 3.0/.38 | 1.0 | 3450/1725 | 230 | 60 | 12.0/4.4 | *TT505 | 56Y | 10.83 | 41 | |
| 4.0/.50 | 1.0 | 3450/1725 | 230 | 60 | 16.4/4.8 | *TT506 | 56Y | 11.58 | 45 | |
| 5.0/.63 | 1.0 | 3450/1725 | 230 | 60 | 19.5/5.0 | *TT507 | 56Y | 12.08 | 48 | |

Notes:

1) Capacitor start design

*Meets California Energy Commission Appliance Regulations 2008 (Publication Number CEC-400-2006-002-REV1)

extreme-E Extreme-E® motors represent our most efficient running, highest performing line of motors.

