Capacitor Start Belted Fan & Blower
Open Drip Proof, Resilient Base

APPLICATIONS:

Designed to meet manufacturer's requirements for belted fans and blowers.

FEATURES:

- 40°C Ambient
- Class A Insulation
- Reversible Rotation
- Suitable For All Angle Operation (Within Blower Housing)
- Automatic Reset Thermal Overload Protector (unless noted)
- Threaded Conduit Hole, Except 299
- **Discount Symbol: DS-3HAC**



HP	RPM	Voltage	Catalog Number	List	Bearings	NEMA Frame	Amps	Shaft N	Shaft U	Protector	Total C	SF	Ship Wt.	Notes
1/4	1140	115/208-230	BD14CA3J9	$305	Ball	56	6.4/3.0-3.2	1.9	0 .625	Auto	11.31	1.35	32	
1/3	1725	115/230	180	$251	Ball	48	6.0/3.0	1.5	0.500	Auto	9.9	1.35	18	
1/2	3450	115/208-230	298	$299	Ball	48	8 .6/4 .3	1 .5	.500	Auto	9 .9	1 .25	16	
	1725	100-120/200-240	6309	$353	Ball	56	6 .3-5 .6/3 .1-2 .8	1.9	0.625	Auto	10.8	1.25	26	18,24,98
	1725	115/208-230	1790	$317	Ball	56	7 .4/3 .7	1 .9	.625	Auto	9 .3	1 .25	27	
3/4	3450	115/208-230	430	$316	Ball	48	9 .2/4 .6	1 .5	.500	Auto	10 .4	1 .25	19	
	1725	100-120/200-240	6313	$403	Ball	56	9 .2-8 .4/4 .6-4 .2	1.9	0.625	Auto	11.3	1.25	32	18,24,98
	1725	115/208-230	1893	$389	Ball	56	11.4/5.7	1.9	0.625	Auto	10.8	1.25	27	
1	3450	115/208-230	431	$344	Ball	48Z	11 .6/5 .8	1 .9	.625	Auto	11 .3	1 .25	13	
	1725	100-120/200-240	6317	$499	Ball	56	12 .3-10 .8/6 .2	1.9	0.625	Auto	12.3	1.15	38	18,24,98
	1725	115/230	3187C	$417	Ball	56	14 .0/7 .0	1 .9	.625	Auto	11 .8	1 .25	23	80
	1725	115/208-230	1769	$476	Ball	56	14.0/7.0	1.9	0.625	Auto	11.8	1.25	30	
1-1/2	3450	115/230	299	$464	Ball	56	17 .2/9 .0	1 .9	.625	Auto	11 .9	1 .15	33	
	1725	115/208-230	4242	$514	Ball	56	22.4/11.2	1.9	0.625	Auto	12.8	1.15	40	
2	3450	115/208-230	399	$324	Ball	56	18.4/10.1-9.2	1.9	0 .625	Auto	12.8	1.2	37	

Note 18: Incorporates Run Capacitor
Note 24: Automatic Reset Thermal Overload Protector
Note 80: Canadian Standard — Connected CCWLE (Reversible)
Note 98: 50/60 Hz Motor